

OVER VIEW

EN .V8

SIBU | DESIGN
we decorate.

NA
non-adhesive

SA
self-adhesive

FR
flame-retardant version
available on request

PRD
digital printing possible

PRS
screen printing possible

PR+
digital/screen printing possible

PR+*
digital/screen printing possible
Prior to printing a corona or plasma
treatment has to be carried out.
By request available in pre-treated version.

PRS*
screen printing possible
Prior to printing a corona or plasma
treatment has to be carried out.
By request available in pre-treated version.

■■■■
wet room suitability

■■■□
limited suitability for wet rooms

AR
abrasion-resistant

AR+
scratch-resistant

+ ▼
entire panel length not shown
in image

Continuous pattern
Continuous pattern

LEATHER-LINE (LL) **15**
FABRIC-LINE (FL) **35**
OPACO-LINE (OL) **43**
SIBUGLAS (SG) **49**
WOOD-LINE (WL) **67**
DECO-LINE (DM) **77**
MULTISTYLE (MS) **115**
STRUCTURE-LINE (SL) **123**
ACRYLIC-LINE (AC) **133**
TRANSLUCENT-LINE (TL) **137**
PUNCH-LINE / 3D (PL/PL3D) **141**
ANTIGRAV **149**

LEGENDE **169**
- PRODUCT CHARACTERISTICS **170**
- EXTRA EQUIPMENT **172**
- PROCESSING **173**
- ACCESSORIES **174**

STORAGE / TRANSPORT GENERAL **175**
CLEANING / DISPOSAL GENERAL **175**

PROCESSING INSTRUCTIONS GENERAL **178**
PROCESSING INSTRUCTIONS **SIBU**GLAS / **OPACO-**LINE **180**
- GLUED AND PRESSED ON ABSORBENT WOOD BASED SHEETS **SIBU**GLAS / **OPACO-**LINE **180**
- BONDED ONTO COATED WOOD BASED SHEETS INCLUDING EDGES AND MILLING **183**
- GLUED AND PRESSED ON ABSORBENT WOOD BASED SHEETS **183**


PROCESSING INSTRUCTIONS **ANTIGRAV** **186**

SIBU | DESIGN
we decorate.

We bring rooms to life.

With our art of laminating, we unite beauty and function by combining different materials.
Customer-oriented and flexible, we manufacture design elements of outstanding quality and thus ensure unique spatial experiences.

LEATHER-LINE



LL CORD
Stony Ground



LL CORD
Dove Tale



LL CORD
Charcoal Light



LL ROMBO 40
Bianco matt



LL ROMBO 40
Creme matt




LL ROMBO 40
Nero matt



LL ROMBO 85
Bianco matt



LL ROMBO 85
Creme matt



LL ROMBO 85
Nero matt




LL CRISTAL
ROMBO 85 Bianco
matt/Silver



LL QUADRO
Bianco matt



LL QUADRO
Creme matt



LL QUADRO
Nero matt




LL QUADRO
LUXURY Bronze



LL COLLAGE
Oro



LL Charcoal
Dark



LL Charcoal
Light



LL Dove Tale



LL London Clay



LL Stony Ground




LL LEGUAN
Silver



LL LEGUAN
Gold



LL LEGUAN
Copper




LL LEGUAN
Nero



LL LEGUAN Silk



LL LEGUAN
Bianco



LL PERSIAN
Gold



LL PERSIAN
Metallic



LL PEARL RAY
Gold



LL FLORAL
White



LL FLORAL
VINTAGE Silver/
Silver



LL FLORAL
White/Silver
matt



LL FLORAL
White/Gold matt



LL FLORAL
Black/Silver matt



LL CURVED
Silver



LL CURVED
Gold



LL CURVED
Rose




LL GRID Silver




LL GRID Gold




LL GRID Rose



LL ALIGNED
Silver



LL ALIGNED
Gold



LL ALIGNED
Rose

FABRIC-LINE



FL CUBE VELVET
Bordeaux



FL CUBE VELVET
Pearl



FL CREPA
VELVET Avocado



FL CREPA
VELVET Volcano



FL COMB
VELVET Curry



FL COMB
VELVET Pearl



FL SQUARE 2
VELVET Mocha



FL SQUARE 2
VELVET Coal



FL LAVA VELVET
Coal



FL LAVA VELVET
Volcano

OPACO-LINE



OL MARBLE
Alpine matt AR



OL GENESIS
White matt AR



OL MARBLE
White matt AR



OL MARBLE
Black matt AR

SIBUGLAS



SG CURVED
Silver AR+



SG CURVED
Gold AR+



SG CURVED
Rose AR+



SG ALIGNED
Silver AR+




SG ALIGNED
Gold AR+



SG ALIGNED
Rose AR+




SG GRID
Silver AR+



SG GRID
Gold AR+



SG GRID
Rose AR+



SG GENESIS
Grey AR+



SG GENESIS
White AR+



SG MARBLE
Brown AR+



SG MARBLE
Alpine AR+




SG MARBLE
Black AR+



SG MARBLE
White AR+



SG MARBLE
Grey AR+




SG MARBLE
Emperador AR+



SG LEGUAN
Bianco met AR+




SG LEGUAN
Silver AR+




SG LEGUAN Silk
AR+



SG LEGUAN
Gold AR+



SG LEGUAN
Copper AR+



SG LEGUAN
Nero AR+



SG VINTAGE
Silver AR+



SG VINTAGE
Copper AR+



SG LUXURY
Gold AR+




SG LUXURY
Bronze AR+



SG OLD Platin
AR+




SG Hollywood




suitable
balancing sheet

WOOD-LINE




WL Carbonized Wood




WL Wenge Wood




WL Maple Alpine




WL Nutwood



WL Nutwood Country



WL Sessile OAK



WL OAK TREE Light

DECO-LINE




DM OXIDIZED Silver AR



DM OXIDIZED Autumn AR



DM OXIDIZED Copper AR



DM OXIDIZED Nickel AR




DM OXIDIZED Platin AR




DM OXIDIZED Titan AR




DM SLIGHTLY USED Gold AR




DM SLIGHTLY USED Bronze AR



DM SLIGHTLY USED Copper AR




DM SLIGHTLY USED Titan AR



DM METALLIC USED Champagne AR




DM METALLIC USED Silver AR




DM METALLIC USED Titan AR




DM METALLIC USED Ivory AR




DM METALLIC USED Sand AR



DM METALLIC USED Bronze AR



DM METALLIC USED Steel AR




DM REFINED METAL Silver AR




DM REFINED METAL Titan AR




DM SILENT Gold AR




DM Iron Age AR



DM CLASSY Silver AR




DM CLASSY Bronze AR



DM CLASSY Copper AR



DM CLASSY Gold AR




DM CLASSY Black AR




DM LUXURY Bronze AR



DM LUXURY Gold AR




DM VINTAGE Copper



DM VINTAGE Silver

DECO-LINE



DM CONCRETE
Grey




DM MONSOON
VINTAGE Brown



DM CEMENT
Light




DM CEMENT
Dark



DM MARBLE
White



DM Travertin



DM GENESIS
Grey supermatt
AR




DM GENESIS
White supermatt
AR




DM MARBLE
White supermatt
AR



DM MARBLE
Black supermatt
AR




DM MAGIC
White AR



DM MAGIC
Black AR



DM Snow White
matt AR



DM Graphite
Black matt AR



DM GALAXY
Silver



DM Hollywood



DM Hollywood
Blue



DM Aqua



DM LUXURY
Holografico

DECO-LINE



DM Silver PF



DM Smoke PF




DM OPTICAL MIRROR Silver AR



DM OPTICAL MIRROR Fashion Grey AR




DM OPTICAL MIRROR Anthracite AR



DM OPTICAL MIRROR Brass AR



DM OPTICAL MIRROR Gold AR



DM OPTICAL MIRROR Copper AR



DM Silver MMS



DM Gold MMS




DM Silver




DM Silver/White



DM Gold AR




DM Rosegold AR



DM Brass AR



DM Anthracite AR



DM Brown AR




DM Rose AR



DM Iceblue AR



DM Fashion Grey AR



DM Bronze



DM Champagne



DM Gold 30




DM Fashion Red



DM Brass brushed matt AR



DM Gold brushed matt AR



DM Silver brushed



DM HGS



DM Champagne brushed



DM Titan brushed



DM Copper brushed



DM DEEP BRUSHED Gravel



DM DEEP BRUSHED Sandy

MULTISTYLE



MS 3x3 flex
Classic Silver



MS 3x3 flex
Classic Gold AR



MS 5x5 flex
Classic Hollywood




MS 5x5 flex
Classic Silver



MS 5x5 flex
Classic Gold AR



MS 5x5 flex
Classic GALAXY
Silver




MS 5x5 flex
Classic MAGIC
White



MS 5x5 flex
Classic MAGIC
Black




MS 10x10 flex
Classic Silver



MS 10x10 flex
Classic Gold AR



MS 20x20 flex
Classic Silver



MS 20x20 flex
Classic Gold AR



MSC 10x10 flex
Classic Silver



MSC 30x30 flex
Classic Silver

STRUCTURE-LINE



SL CRASHED
OLD Platin




SL CRASHED
Silver



SL IMPACT
VINTAGE Silver



SL IMPACT
ANTIQUE Bronze




SL LAVA VINTAGE
Copper




SL RACE
VINTAGE Silver/
Bronze



SL RACE
VINTAGE Copper/
Silver



SL CROCO
Silver PF/Silver



SL CROCO
Smoke PF/Silver



SL SQUARE 3
HGS

ACRYLIC-LINE




AC MOTION
ONE White



AC MOTION
ONE Black



AC MOTION
TWO White



AC MOTION
TWO Black

TRANSLUCENT-LINE



TL LINEA
104x62 OLD
Platin



TL LINEA
104x62 SILENT
Gold

PUNCH-LINE / 3D



PL3D Q-10-30
OLD Platin/Silver



PL3D H-10-30
Pearl White
PF/Gold



PL3D ROSES
Pearl White PF/
Gold



PL3D ROSES
Silver PF/Silver



PL3D Q 10-40-40
Silver PF/Silver



PL3D Q 10-40-40
Smoke PF T1/
Silver matt



PL3D Q 5-15-15
Black T1/Silver



PL Q 5-15-15
Silver PF

ANTIGRAV



FL CREPA
VELVET Avocado
Antigrav



FL CREPA
VELVET Volcano
Antigrav



FL LAVA
VELVET Coal
Antigrav



FL LAVA
VELVET Volcano
Antigrav



FL COMB
VELVET Curry
Antigrav



FL COMB
VELVET Pearl
Antigrav



FL SQUARE 2
VELVET Mocha
Antigrav



FL SQUARE 2
VELVET Coal
Antigrav



FL CUBE VELVET
Bordeaux
Antigrav



FL CUBE
VELVET Pearl
Antigrav



LL LEGUAN
Silver



LL LEGUAN
Gold



LL LEGUAN
Copper




LL LEGUAN
Nero




LL LEGUAN Silk



LL LEGUAN
Bianco



LL CORD
Stony Ground
Antigrav



LL CORD
Dove Tale
Antigrav



LL CORD
Charcoal Light
Antigrav



LL Charcoal
Dark Antigrav



LL Charcoal
Light Antigrav



LL Dove Tale
Antigrav



LL London Clay
Antigrav



LL Stony Ground
Antigrav




DM CEMENT
Dark Antigrav



DM CEMENT
Light Antigrav




DM Travertin
Antigrav




DM MARBLE
White Antigrav




DM CONCRETE
Grey Antigrav



WL OAK TREE
Light Antigrav



WL Nutwood
Antigrav



WL Nutwood
Country Antigrav




WL Maple Alpine
Antigrav



WL Wenge Wood
Antigrav



WL Sessile OAK
Antigrav



WL Carbonized
Wood Antigrav

LEATHER-
LINE



LL CORD Stony Ground
2600 x 1000 / **NA** 19542 / **SA** 19545




LL CORD Dove Tale
2600 x 1000 / **NA** 19532 / **SA** 19544



LL CORD Charcoal Light
2600 x 1000 / **NA** 19543 / **SA** 19546



2600 x 1000



LEATHER-LINE

LL CORD

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PU-leather	
Material thickness mm	2	2,13
Max. relief height mm	3,2	3,33
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Rolled packable *	✓	✓
Wight/Designsheet ~	3,4 kg	3,8 kg

* Design sheets to be rolled with the decor side outwardly (both – NA and SA version). We recommend rolling not more than 3 sheets per carton (480 x 480 mm).

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing	✓	–
Milling	–	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	–	–
Further thicknesses	–	–
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A2

Special colors

On request



□
LL ROMBO 40
Creme matt

Photo: Jesse



□
LL ROMBO 40
Nero matt

LL ROMBO 40 Bianco matt
2600 x 1000 / **NA** 15025 / **SA** 15041



LL ROMBO 40 Creme matt
2600 x 1000 / **NA** 13848 / **SA** 13863




LL ROMBO 40 Nero matt
2600 x 1000 / **NA** 15014 / **SA** 15029

LEATHER-LINE

LL ROMBO 40

2600 x 1000



Product characteristics

	NA	SA
Base material	HIPS, PE-foam	
Surface material	PU-leather	
Material thickness mm	3,8	4,04
Max. relief height mm	5,0	5,24
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Rolled packable *	✓	✓

* Design sheets to be rolled with the decor side outwardly (both – NA and SA version). We recommend rolling not more than 3 sheets per carton (480 x 480 mm).

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	–	–
Laser cutting	✓	✓
Hot bending	–	–
PVA compressible	–	–
Smallest bending radius	300 mm	300 mm

Extra equipment

	NA	SA
Special formats	–	–
Further thicknesses	–	–
Cuttings	✓	✓
Magnetic	–	
PVA pre-treatment	–	–

Accessories

SIBUKLE	Spatula A2


Special colors

On request

LL ROMBO 85 Bianco matt
2600 x 1000 / **NA** 15026 / **SA** 15042



LL ROMBO 85 Creme matt
2600 x 1000 / **NA** 13852 / **SA** 13867




LL ROMBO 85 Nero matt
2600 x 1000 / **NA** 15015 / **SA** 15030



□
LL ROMBO 85
Creme matt

Photo: Boris Breuer - CABINET Schranksysteme AG

2600 x 1000



LEATHER-LINE

LL ROMBO 85

Product characteristics

	NA	SA
Base material	HIPS, PE-foam	
Surface material	PU-leather	
Material thickness mm	3,8	4,04
Max. relief height mm	5,0	5,24
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Rolled packable *	✓	✓

* Design sheets to be rolled with the decor side outwardly (both – NA and SA version). We recommend rolling not more than 3 sheets per carton (480 x 480 mm).

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	–	–
Laser cutting	✓	✓
Hot bending	–	–
PVA compressible	–	–
Smallest bending radius	300 mm	300 mm

Extra equipment

	NA	SA
Special formats	–	–
Further thicknesses	–	–
Cuttings	✓	✓
Magnetic	–	
PVA pre-treatment	–	–

Accessories

SIBUKLE	Spatula A2

Special colors

On request



□
LL CRISTAL ROMBO 85
Bianco matt/Silver

Photo: Cary Horowitz




LL CRISTAL ROMBO 85 Bianco matt/Silver
2600 x 1000 / **SA** 15044

LEATHER-LINE

LL CRISTAL ROMBO 85

2600 x 1000



+ ▾

Product characteristics

	SA
Base material	HIPS, PE-foam
Surface material	PU-leather, crystal: PMMA
Material thickness mm	4,04
Max. relief height mm	5,24
Temperature stability	up to 60 °C
Wet room suitability	■■■□
Rolled packable *	✓

* Design sheets to be rolled with the decor side outwardly (both – NA and SA version). We recommend rolling not more than 3 sheets per carton (480 x 480 mm).

Processing

	SA
Cutting, punching	✓
Drilling	✓
Sawing, milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	–
Smallest bending radius	300 mm

Extra equipment

	SA
Special formats	–
Further thicknesses	–
Cuttings	✓
Magnetic	–
PVA pre-treatment	–

Accessories

SIBUKLE	Spatula A2

Special colors

On request

LL QUADRO Bianco matt
2600 x 1000 / **NA** 16420 / **SA** 15175



LL QUADRO Creme matt
2600 x 1000 / **NA** 14273 / **SA** 14277




LL QUADRO Nero matt
2600 x 1000 / **NA** 15017 / **SA** 15032





2600 x 1000



LEATHER-LINE

LL QUADRO

Product characteristics

	NA	SA
Base material	HIPS, PE-foam	
Surface material	PU-leather	
Material thickness mm	2,8	3,04
Max. relief height mm	4,8	5,04
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Rolled packable *	✓	✓

* Design sheets to be rolled with the decor side outwardly (both – NA and SA version). We recommend rolling not more than 3 sheets per carton (480 x 480 mm).

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	–	–
Laser cutting	✓	✓
Hot bending	–	–
PVA compressible	–	–
Smallest bending radius	300 mm	300 mm

Extra equipment

	NA	SA
Special formats	–	–
Further thicknesses	–	–
Cuttings	✓	✓
Magnetic	–	
PVA pre-treatment	–	–

Accessories

SIBUKLE	Spatula A2

Special colors

On request



□
LL QUADRO
LUXURY Bronze




LL QUADRO LUXURY Bronze
2600 x 1000 / **NA** 17831 / **SA** 17851

LEATHER-LINE

LL QUADRO

2600 x 1000



Product characteristics

	NA	SA
Base material	HIPS, PE-foam	
Surface material	PU-leather	
Material thickness mm	2,8	3,04
Max. relief height mm	4,8	5,04
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Rolled packable *	✓	✓

* Design sheets to be rolled with the decor side outwardly (both – NA and SA version). We recommend rolling not more than 3 sheets per carton (480 x 480 mm).

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	–	–
Laser cutting	✓	✓
Hot bending	–	–
PVA compressible	–	–
Smallest bending radius	300 mm	300 mm

Extra equipment

	NA	SA
Special formats	–	–
Further thicknesses	–	–
Cuttings	✓	✓
Magnetic	–	
PVA pre-treatment	–	–

Accessories

SIBUKLE	Spatula A2

Special colors

On request




LL COLLAGE Oro
2600 x 1000 / 1,9 / **NA** 13923 / **SA** 13926



□
LL COLLAGE Oro

2600 x 1000



LEATHER-LINE

LL COLLAGE

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PU-leather	
Material thickness mm	1,9	2,15
Max. relief height mm	3,5	3,75
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Rolled packable *	✓	✓

* Design sheets to be rolled with the decor side outwardly (both – NA and SA version). We recommend rolling not more than 3 sheets per carton (480 x 480 mm).

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing	✓	–
Milling	–	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	–	–
Further thicknesses	–	–
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment Oro	–	–

Accessories

SIBUKLE	Spatula A2

Special colors

On request



Photo: © istock.com

LEATHER-LINE

LEATHER-LINE

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PU-leather	
Material thickness mm	1,95	2,08
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Rolled packable *	✓	✓

* Design sheets to be rolled with the decor side outwardly (both – NA and SA version). We recommend rolling not more than 3 sheets per carton (480 x 480 mm).

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing	✓	–
Milling	–	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories


SIBUKLE	Spatula A1

Special colors


On request




LL Charcoal Dark
2600 x 1000 / **NA** 19299 / **SA** 19302



LL Charcoal Light
2600 x 1000 / **NA** 19298 / **SA** 19301



LL Dove Tale
2600 x 1000 / **NA** 19013 / **SA** 19024



LL London Clay
2600 x 1000 / **NA** 19014 / **SA** 19025



LL Stony Ground
2600 x 1000 / **NA** 19012 / **SA** 19023




LL LEGUAN Silver
2600 x 1000 / **NA** 12883 / **SA** 12893



LL LEGUAN Gold
2600 x 1000 / **NA** 13480 / **SA** 13478




LL LEGUAN Copper
2600 x 1000 / **NA** 12884 / **SA** 12894



LL LEGUAN Nero
2600 x 1000 / **NA** 14778 / **SA** 14797

2600 x 1000





□
LL LEGUAN Silver

LEATHER-LINE

LL LEGUAN

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PU-leather	
Material thickness mm	1,5	1,63
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Rolled packable *	✓	✓

* Design sheets to be rolled with the decor side outwardly (both – NA and SA version). We recommend rolling not more than 3 sheets per carton (480 x 480 mm).

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing	✓	–
Milling	–	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–



□
LL LEGUAN Bianco



LL LEGUAN Silk
2600 x 1000 / 1,5 mm / **NA** 16451 / **SA** 16452



LL LEGUAN Bianco
2600 x 1000 / 1,4 mm / **NA** 15609 / **SA** 15610

LEATHER-LINE

LL LEGUAN

2600 x 1000



Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PU-leather	
Material thickness mm	1,4 / 1,5	1,53 / 1,63
Temperature stability	up to 60 °C	
Wet room suitability	Silk	■■■□
	Bianco	■■■■
Rolled packable *	✓	✓

* Design sheets to be rolled with the decor side outwardly (both – NA and SA version). We recommend rolling not more than 3 sheets per carton (480 x 480 mm).

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing	✓	–
Milling	–	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment


	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors


–



LL PERSIAN Gold
2600 x 1000 / **NA** 15656 / **SA** 15660



LL PERSIAN Metallic
2600 x 1000 / **NA** 15655 / **SA** 15659



□
LL PERSIAN Gold

2600 x 1000



LEATHER-LINE

LL PERSIAN

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PU-leather	
Material thickness mm	1,9	2,03
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Rolled packable *	✓	✓

* Design sheets to be rolled with the decor side outwardly (both – NA and SA version). We recommend rolling not more than 3 sheets per carton (480 x 480 mm).

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing	✓	–
Milling	–	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories


SIBUKLE	Spatula A2

Special colors

–



Photo: © Kaupo Kikkas




LL PEARL RAY Gold
2600 x 1000 / **NA** 17015 / **SA** 17016

LEATHER-LINE

LL PEARL RAY

2600 x 1000



Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PU-leather	
Material thickness mm	1,6	1,73
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Rolled packable *	✓	✓

* Design sheets to be rolled with the decor side outwardly (both – NA and SA version). We recommend rolling not more than 3 sheets per carton (480 x 480 mm).

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing	✓	–
Milling	–	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

On request



LL FLORAL White
2600 x 1000 / **NA** 13470 / **SA** 13473



Photo: Wippro

2600 x 1000



LEATHER-LINE

LL FLORAL

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PU-leather	
Material thickness mm	2,1	2,23
Max. relief height mm	2,9	3,03
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Rolled packable *	✓	✓

* Design sheets to be rolled with the decor side outwardly (both – NA and SA version). We recommend rolling not more than 3 sheets per carton (480 x 480 mm).

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing	✓	–
Milling	–	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	–	–
Further thicknesses	–	–
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A2

Special colors

On request





LL FLORAL VINTAGE Silver/Silver
2600 x 1000 / **NA** 17266 / **SA** 17267



LL FLORAL White/Silver matt
2600 x 1000 / **NA** 13418 / **SA** 13414



LL FLORAL White/Gold matt
2600 x 1000 / **NA** 13419 / **SA** 13415



LL FLORAL Black/Silver matt
2600 x 1000 / **NA** 13416 / **SA** 13412

LEATHER-LINE

LL FLORAL

2600 x 1000



Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PU-leather	
Material thickness mm	1,9	2,03
Max. relief height mm	2,9	3,03
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Rolled packable *	✓	✓

* Design sheets to be rolled with the decor side outwardly (both – NA and SA version). We recommend rolling not more than 3 sheets per carton (480 x 480 mm).

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing	✓	–
Milling	–	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	–	–
Further thicknesses	–	–
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A2

Special colors

On request




LL CURVED Silver
2600 x 1000 / **NA** 22805 / **SA** 22806



LL CURVED Gold
2600 x 1000 / **NA** 22803 / **SA** 22808



LL CURVED Rose
2600 x 1000 / **NA** 22804 / **SA** 22807



2600 x 1000



LEATHER-LINE

LL CURVED

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PU-leather	
Material thickness mm	1,7	1,83
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Rolled packable *	✓	✓

* Design sheets to be rolled with the decor side outwardly (both – NA and SA version). We recommend rolling not more than 3 sheets per carton (480 x 480 mm).

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing	✓	–
Milling	–	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–





LL GRID Silver
2600 x 1000 / **NA** 22811 / **SA** 22812



LL GRID Gold
2600 x 1000 / **NA** 22809 / **SA** 22814



LL GRID Rose
2600 x 1000 / **NA** 22810 / **SA** 22813

LEATHER-LINE

LL GRID

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PU-leather	
Material thickness mm	1,7	1,83
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Rolled packable *	✓	✓

* Design sheets to be rolled with the decor side outwardly (both – NA and SA version). We recommend rolling not more than 3 sheets per carton (480 x 480 mm).

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing	✓	–
Milling	–	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–


Accessories

SIBUKLE	Spatula A1

Special colors

–

2600 x 1000





LL ALIGNED Silver
2600 x 1000 / **NA** 22817 / **SA** 22818



LL ALIGNED Gold
2600 x 1000 / **NA** 22815 / **SA** 22820



LL ALIGNED Rose
2600 x 1000 / **NA** 22816 / **SA** 22819



2600 x 1000



LEATHER-LINE

LL ALIGNED

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PU-leather	
Material thickness mm	1,7	1,83
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Rolled packable *	✓	✓

* Design sheets to be rolled with the decor side outwardly (both – NA and SA version). We recommend rolling not more than 3 sheets per carton (480 x 480 mm).

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing	✓	–
Milling	–	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–



Photo: © istock.com

FABRIC-
LINE

SIBU | DESIGN
we decorate.



FL CUBE VELVET Bordeaux
2600 x 1000 / **NA** 22709 / **SA** 22719



FL CUBE VELVET Pearl
2600 x 1000 / **NA** 22710 / **SA** 22720

Please consider the nap direction of the surface before further processing or product installation. If design panels are not installed in the same direction, there will be a visual color difference.


FL CUBE VELVET Pearl

Photo: © istock.com

2600 x 1000



FABRIC-LINE

FL CUBE VELVET

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PET fiber	
Material thickness mm	1,7	1,83
Max. relief height mm	2,2	2,33
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Rolled packable *	✓	✓

* Design sheets to be rolled with the decor side outwardly (both – NA and SA version). We recommend rolling not more than 3 sheets per carton (480 x 480 mm).

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing	✓	–
Milling	–	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Cuttings	✓	✓
Magnetic from 3 sheets **	✓	
PVA pre-treatment	✓	–

** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A2

Special colors

On request



FL CREPA VELVET Volcano

Photo: © istock.com



FL CREPA VELVET Avocado
2600 x 1000 / **NA** 22705 / **SA** 22715



FL CREPA VELVET Volcano
2600 x 1000 / **NA** 22706 / **SA** 22717

Please consider the nap direction of the surface before further processing or product installation. If design panels are not installed in the same direction, there will be a visual color difference.

FABRIC-LINE

FL CREPA VELVET

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PET fiber	
Material thickness mm	1,7	1,83
Max. relief height mm	2,2	2,33
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Rolled packable *	✓	✓

* Design sheets to be rolled with the decor side outwardly (both – NA and SA version). We recommend rolling not more than 3 sheets per carton (480 x 480 mm).

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing	✓	–
Milling	–	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Cuttings	✓	✓
Magnetic from 3 sheets **	✓	
PVA pre-treatment	✓	–

** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A2

Special colors

On request

2600 x 1000





FL COMB VELVET Curry
2600 x 1000 / **NA** 22695 / **SA** 22711



FL COMB VELVET Pearl
2600 x 1000 / **NA** 22696 / **SA** 22712

Please consider the nap direction of the surface before further processing or product installation. If design panels are not installed in the same direction, there will be a visual color difference.



2600 x 1000



FABRIC-LINE

FL COMB VELVET

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PET fiber	
Material thickness mm	1,7	1,83
Max. relief height mm	2,2	2,33
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Rolled packable *	✓	✓

* Design sheets to be rolled with the decor side outwardly (both – NA and SA version). We recommend rolling not more than 3 sheets per carton (480 x 480 mm).

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing	✓	–
Milling	–	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Cuttings	✓	✓
Magnetic from 3 sheets **	✓	
PVA pre-treatment	✓	–

** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories


SIBUKLE	Spatula A2

Special colors

On request



Photo: © istock.com



FL SQUARE 2 VELVET Mocha
2600 x 1000 / **NA** 22703 / **SA** 22713




FL SQUARE 2 VELVET Coal
2600 x 1000 / **NA** 22704 / **SA** 22714

Please consider the nap direction of the surface before further processing or product installation. If design panels are not installed in the same direction, there will be a visual color difference.

FABRIC-LINE

FL SQUARE 2 VELVET

2600 x 1000



Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PET fiber	
Material thickness mm	1,7	1,83
Max. relief height mm	2,2	2,33
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Rolled packable *	✓	✓

* Design sheets to be rolled with the decor side outwardly (both – NA and SA version). We recommend rolling not more than 3 sheets per carton (480 x 480 mm).

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing	✓	–
Milling	–	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Cuttings	✓	✓
Magnetic from 3 sheets **	✓	
PVA pre-treatment	✓	–

** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A2

Special colors

On request



FL LAVA VELVET Volcano
2600 x 1000 / **NA** 22707 / **SA** 22718



FL LAVA VELVET Coal
2600 x 1000 / **NA** 22708 / **SA** 22716


Please consider the nap direction of the surface before further processing or product installation. If design panels are not installed in the same direction, there will be a visual color difference.



FL LAVA VELVET Volcano

Photo: © istock.com

2600 x 1000



+ ▾

FABRIC-LINE

FL LAVA VELVET

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PET fiber	
Material thickness mm	1,7	1,83
Max. relief height mm	2,2	2,33
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Rolled packable *	✓	✓

* Design sheets to be rolled with the decor side outwardly (both – NA and SA version). We recommend rolling not more than 3 sheets per carton (480 x 480 mm).

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing	✓	–
Milling	–	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Cuttings	✓	✓
Magnetic from 3 sheets **	✓	
PVA pre-treatment	✓	–

** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A2

Special colors

On request



FL LAVA VELVET Volcano

OPACO-
LINE

SIBU | DESIGN
we decorate.



OL MARBLE Alpine matt AR
2600 x 1000 / **NA** 22624 / **SA** 22632



2600 x 1000



OPACO LINE

OL MARBLE Alpine matt AR

Product characteristics

	NA	SA
Surface material	PET	
Base material	PS	
Back side material	Paper	
Material thickness mm	2,3	2,43
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■□	
Rolled packable	–	–

Processing

	NA	SA
Cutting, punching	–	–
Drilling	✓	✓
Sawing, milling (supported by a panel)	✓	✓
Laser cutting	✓	✓
Hot bending	–	–
PVA compressible	✓	–
Smallest bending radius	1000 mm	1000 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets **	✓	
PVA pre-treatment	–	–

Accessories

SIBUKLE	Spatula A2

Special colors

–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).



☐ OL GENESIS White matt AR



PRS*

OL GENESIS White matt AR
2600 x 1000 / **NA** 22626 / **SA** 22634

OPACO LINE

OL GENESIS White matt AR

2600 x 1000



+ ▾

Product characteristics

	NA	SA
Surface material	PET	
Base material	PS	
Back side material	Paper	
Material thickness mm	2,3	2,43
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■□	
Rolled packable	–	–

Processing

	NA	SA
Cutting, punching	–	–
Drilling	✓	✓
Sawing, milling (supported by a panel)	✓	✓
Laser cutting	✓	✓
Hot bending	–	–
PVA compressible	✓	–
Smallest bending radius	1000 mm	1000 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets **	✓	
PVA pre-treatment	–	–

Accessories

SIBUKLE	Spatula A2

Special colors

–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).



OL MARBLE White matt AR
2600 x 1000 / **NA** 22625 / **SA** 22633



□
OL MARBLE White matt AR

Photo: © istock.com

2600 x 1000



OPACO LINE

OL MARBLE White matt AR

Product characteristics

	NA	SA
Surface material	PET	
Base material	PS	
Back side material	Paper	
Material thickness mm	2,3	2,43
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■□	
Rolled packable	–	–

Processing

	NA	SA
Cutting, punching	–	–
Drilling	✓	✓
Sawing, milling (supported by a panel)	✓	✓
Laser cutting	✓	✓
Hot bending	–	–
PVA compressible	✓	–
Smallest bending radius	1000 mm	1000 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets **	✓	
PVA pre-treatment	–	–

Accessories

SIBUKLE	Spatula A2

Special colors

–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).





OL MARBLE Black matt AR
2600 x 1000 / **NA** 22627 / **SA** 22635

OPACO LINE

OL MARBLE Black matt AR

2600 x 1000



Product characteristics

	NA	SA
Surface material	PET	
Base material	PS	
Back side material	Paper	
Material thickness mm	2,3	2,43
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■□	
Rolled packable	–	–

Processing

	NA	SA
Cutting, punching	–	–
Drilling	✓	✓
Sawing, milling (supported by a panel)	✓	✓
Laser cutting	✓	✓
Hot bending	–	–
PVA compressible	✓	–
Smallest bending radius	1000 mm	1000 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets **	✓	
PVA pre-treatment	–	–

Accessories

SIBUKLE	Spatula A2

Special colors

–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

SIBUGLAS

SIBU | DESIGN
we decorate.



SG CURVED Silver AR+
2600 x 1000 / **NA** 20177 / **SA** 20215



SG CURVED Gold AR+
2600 x 1000 / **NA** 20176 / **SA** 20214



SG CURVED Rose AR+
2600 x 1000 / **NA** 20178 / **SA** 20216


SG CURVED Silver AR+

Photo: © istock.com

2600 x 1000



SIBUGLAS scratch-resistant

SG CURVED AR+

Product characteristics

	NA	SA
Surface material = Base material	PMMA AR+	
Back side material	PU-leather	
Material thickness mm	2,9	3,03
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Abrasion resistance	■■■■■■■■	
Rolled packable	–	–

Processing

	NA	SA
Cutting, punching	–	–
Drilling	✓	✓
Sawing	✓	✓
Milling	–	–
Laser cutting	✓	✓
Hot bending	–	–
PVA compressible	✓	–
Smallest bending radius	1000 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets*	✓	
PVA pre-treatment	–	–

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A2

Special colors

–





SG ALIGNED Silver AR+
2600 x 1000 / **NA** 20180 / **SA** 20219



SG ALIGNED Gold AR+
2600 x 1000 / **NA** 20179 / **SA** 20218



SG ALIGNED Rose AR+
2600 x 1000 / **NA** 20181 / **SA** 20217

SIBUGLAS scratch-resistant

SG ALIGNED AR+

2600 x 1000



Product characteristics

	NA	SA
Surface material = Base material	PMMA AR+	
Back side material	PU-leather	
Material thickness mm	2,9	3,03
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Abrasion resistance	■■■■■■■■	
Rolled packable	–	–

Processing

	NA	SA
Cutting, punching	–	–
Drilling	✓	✓
Sawing	✓	✓
Milling	–	–
Laser cutting	✓	✓
Hot bending	–	–
PVA compressible	✓	–
Smallest bending radius	1000 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets*	✓	
PVA pre-treatment	–	–

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A2

Special colors

–



SG GRID Silver AR+
2600 x 1000 / **NA** 20183 / **SA** 20222




SG GRID Gold AR+
2600 x 1000 / **NA** 20182 / **SA** 20221



SG GRID Rose AR+
2600 x 1000 / **NA** 20184 / **SA** 20220



2600 x 1000



SIBUGLAS scratch-resistant

SG GRID AR+

Product characteristics

	NA	SA
Surface material = Base material	PMMA AR+	
Back side material	PU-leather	
Material thickness mm	2,9	3,03
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Abrasion resistance	■■■■■■■■	
Rolled packable	–	–

Processing

	NA	SA
Cutting, punching	–	–
Drilling	✓	✓
Sawing	✓	✓
Milling	–	–
Laser cutting	✓	✓
Hot bending	–	–
PVA compressible	✓	–
Smallest bending radius	1000 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets*	✓	
PVA pre-treatment	–	–

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A2

Special colors

–



Photo: © istock.com



SG GENESIS Grey AR+
2600 x 1000 / **NA** 20185 / **SA** 20223



SG GENESIS White AR+
2600 x 1000 / **NA** 23177 / **SA** 23180

SIBUGLAS scratch-resistant

SG GENESIS Grey AR+

2600 x 1000



Product characteristics

	NA	SA
Surface material = Base material	PMMA AR+	
Back side material	Paper	
Material thickness mm	2,3	2,43
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Abrasion resistance	■■■■■■■■	
Rolled packable	–	–

Processing

	NA	SA
Cutting, punching	–	–
Drilling	✓	✓
Sawing, milling (supported by a panel)	✓	✓
Laser cutting	✓	✓
Hot bending	–	–
PVA compressible	✓	–
Smallest bending radius	1000 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets *	✓	
PVA pre-treatment	–	–

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A2

Special colors

–



SG MARBLE Brown AR+
2600 x 1000 / **NA** 19331 / **SA** 19342



2600 x 1000



SIBUGLAS scratch-resistant

SG MARBLE Brown AR+

Product characteristics

	NA	SA
Surface material = Base material	PMMA AR+	
Back side material	Paper	
Material thickness mm	2,3	2,43
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Abrasion resistance	■■■■■■■■	
Rolled packable	–	–

Processing

	NA	SA
Cutting, punching	–	–
Drilling	✓	✓
Sawing, milling (supported by a panel)	✓	✓
Laser cutting	✓	✓
Hot bending	–	–
PVA compressible	✓	–
Smallest bending radius	1000 mm	1000 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets *	✓	
PVA pre-treatment	–	–

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A2

Special colors

–





SG MARBLE Alpine AR+
2600 x 1000 / **NA** 19329 / **SA** 19340

SIBUGLAS scratch-resistant

SG MARBLE Alpine AR+

2600 x 1000



Product characteristics

	NA	SA
Surface material = Base material	PMMA AR+	
Back side material	Paper	
Material thickness mm	2,3	2,43
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Abrasion resistance	■■■■■■■■	
Rolled packable	–	–

Processing

	NA	SA
Cutting, punching	–	–
Drilling	✓	✓
Sawing, milling (supported by a panel)	✓	✓
Laser cutting	✓	✓
Hot bending	–	–
PVA compressible	✓	–
Smallest bending radius	1000 mm	1000 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets *	✓	
PVA pre-treatment	–	–

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories


SIBUKLE	Spatula A2

Special colors

–



SG MARBLE Black AR+
2600 x 1000 / **NA** 19330 / **SA** 19341



2600 x 1000



SIBUGLAS scratch-resistant

SG MARBLE Black AR+

Product characteristics

	NA	SA
Surface material = Base material	PMMA AR+	
Back side material	Paper	
Material thickness mm	2,3	2,43
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Abrasion resistance	■■■■■■■■	
Rolled packable	–	–

Processing

	NA	SA
Cutting, punching	–	–
Drilling	✓	✓
Sawing, milling (supported by a panel)	✓	✓
Laser cutting	✓	✓
Hot bending	–	–
PVA compressible	✓	–
Smallest bending radius	1000 mm	1000 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets *	✓	
PVA pre-treatment	–	–

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A2

Special colors

–



□
SG MARBLE White AR+

Photo: © fotolia.com



SG MARBLE White AR+
2600 x 1000 / **NA** 19334 / **SA** 19345

SIBUGLAS scratch-resistant

SG MARBLE White AR+

2600 x 1000



Product characteristics

	NA	SA
Surface material = Base material	PMMA AR+	
Back side material	Paper	
Material thickness mm	2,3	2,43
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Abrasion resistance	■■■■■■■■	
Rolled packable	–	–

Processing

	NA	SA
Cutting, punching	–	–
Drilling	✓	✓
Sawing, milling (supported by a panel)	✓	✓
Laser cutting	✓	✓
Hot bending	–	–
PVA compressible	✓	–
Smallest bending radius	1000 mm	1000 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets *	✓	
PVA pre-treatment	–	–

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A2

Special colors

–



SG MARBLE Grey AR+
2600 x 1000 / **NA** 19333 / **SA** 19344



□ SG MARBLE Grey AR+

Photo: © shutterstock.com

2600 x 1000



SIBUGLAS scratch-resistant

SG MARBLE Grey AR+

Product characteristics

	NA	SA
Surface material = Base material	PMMA AR+	
Back side material	Paper	
Material thickness mm	2,3	2,43
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Abrasion resistance	■■■■■■■■	
Rolled packable	–	–

Processing

	NA	SA
Cutting, punching	–	–
Drilling	✓	✓
Sawing, milling (supported by a panel)	✓	✓
Laser cutting	✓	✓
Hot bending	–	–
PVA compressible	✓	–
Smallest bending radius	1000 mm	1000 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets *	✓	
PVA pre-treatment	–	–

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A2

Special colors

–



SG MARBLE Emperador AR+

Photo: © istock.com




SG MARBLE Emperador AR+
2600 x 1000 / **NA** 19332 / **SA** 19343

SIBUGLAS scratch-resistant

SG MARBLE Emperador AR+

2600 x 1000



Product characteristics

	NA	SA
Surface material = Base material	PMMA AR+	
Back side material	Paper	
Material thickness mm	2,3	2,43
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Abrasion resistance	■■■■■■■■	
Rolled packable	–	–

Processing

	NA	SA
Cutting, punching	–	–
Drilling	✓	✓
Sawing, milling (supported by a panel)	✓	✓
Laser cutting	✓	✓
Hot bending	–	–
PVA compressible	✓	–
Smallest bending radius	1000 mm	1000 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets *	✓	
PVA pre-treatment	–	–

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A2

Special colors

–



SG LEGUAN Bianco met AR+
2600 x 1000 / **NA** 19304 / **SA** 19305




SG LEGUAN Silver AR+
2600 x 1000 / **NA** 16975 / **SA** 16979




SG LEGUAN Silk AR+
2600 x 1000 / **NA** 20275 / **SA** 20276




SG LEGUAN Gold AR+
2600 x 1000 / **NA** 16977 / **SA** 16982



SG LEGUAN Copper AR+
2600 x 1000 / **NA** 16976 / **SA** 16981



SG LEGUAN Nero AR+
2600 x 1000 / **NA** 18089 / **SA** 18095


SG LEGUAN Nero AR+

SIBUGLAS scratch-resistant

SG LEGUAN AR+

Product characteristics

	NA	SA
Surface material = Base material	PMMA AR+	
Back side material	PU-leather	
Material thickness mm	2,8	2,93
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Abrasion resistance	■■■■■■■■	
Rolled packable	–	–

Processing

	NA	SA
Cutting, punching	–	–
Drilling	✓	✓
Sawing (supported by a panel)	✓	✓
Milling	–	–
Laser cutting	✓	✓
Hot bending	–	–
PVA compressible	✓	–
Smallest bending radius	1000 mm	1000 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets *	✓	
PVA pre-treatment	–	–

* Ground must be real metal or a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A2

Special colors

On request



SG VINTAGE Copper AR+

Photo: © tamix115 - fotolia.com



SG VINTAGE Silver AR+
2600 x 1000 / **NA** 17197 / **SA** 17199



SG VINTAGE Copper AR+
2600 x 1000 / **NA** 17198 / **SA** 17200

SIBUGLAS scratch-resistant

SG VINTAGE AR+

2600 x 1000



Product characteristics

	NA	SA
Surface material = Base material	PMMA AR+	
Back side material	PU-leather	
Material thickness mm	2,8	2,93
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Abrasion resistance	■■■■■■■■	
Rolled packable	–	–

Processing

	NA	SA
Cutting, punching	–	–
Drilling	✓	✓
Sawing (supported by a panel)	✓	✓
Milling	–	–
Laser cutting	✓	✓
Hot bending	–	–
PVA compressible	✓	–
Smallest bending radius	1000 mm	1000 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets *	✓	
PVA pre-treatment	–	–

* Ground must be real metal or a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A2

Special colors

–



SG LUXURY Gold AR+
2600 x 1000 / **NA** 17819 / **SA** 17840



SG LUXURY Bronze AR+
2600 x 1000 / **NA** 17820 / **SA** 17841



SG LUXURY Gold AR+

2600 x 1000



SIBUGLAS **scratch-resistant**

SG LUXURY AR+

Product characteristics

	NA	SA
Surface material = Base material	PMMA AR+	
Back side material	PU-leather	
Material thickness mm	3,1	3,23
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Abrasion resistance	■■■■■■■■	
Rolled packable	–	–

Processing

	NA	SA
Cutting, punching	–	–
Drilling	✓	✓
Sawing (supported by a panel)	✓	✓
Milling	–	–
Laser cutting	✓	✓
Hot bending	–	–
PVA compressible	✓	–
Smallest bending radius	1000 mm	1000 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets *	✓	
PVA pre-treatment	–	–

* Ground must be real metal or a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A2

Special colors

On request



□
SG OLD Platin AR+



SG OLD Platin AR+
2600 x 1000 / **NA** 18067 / **SA** 18001

SIBUGLAS scratch-resistant

SG OLD Platin AR+

2600 x 1000



Product characteristics

	NA	SA
Surface material = Base material	PMMA AR+	
Back side material	PU-leather	
Material thickness mm	3,1	3,23
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Abrasion resistance	■■■■■■■■	
Rolled packable	–	–

Processing

	NA	SA
Cutting, punching	–	–
Drilling	✓	✓
Sawing (supported by a panel)	✓	✓
Milling	–	–
Laser cutting	✓	✓
Hot bending	–	–
PVA compressible	✓	–
Smallest bending radius	1000 mm	1000 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets *	✓	
PVA pre-treatment	–	–

* Ground must be real metal or a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A2

Special colors

–



SG Hollywood
2600 x 1000 / **NA** 23116

On the protective film of the reverse side is a label "Reverse side / Processing side". SG Hollywood always has to be processed from the reverse side.


SG Hollywood

Photo: © Form Factory

SIBUGLAS

SG Hollywood

Product characteristics

	NA
Surface material = Base material	PMMA
Back side material	PET
Material thickness mm	3,1
Temperature stability	up to 60 °C
Wet room suitability	■■■■
Abrasion resistance	■■■■□□
Rolled packable	–

Processing

	NA
Cutting, punching	–
Drilling	✓
Sawing, milling (supported by a panel)	✓
Laser cutting	✓
Hot bending*	On request
Thermoforming	On request
Smallest bending radius	1000 mm

* Only an inner corner on the visible side is possible by heating the reverse side!

Extra equipment

	NA
Special formats	On request
Further thicknesses	On request
Cuttings	✓

Special colors

–



SG Hollywood

Photo: Foam Factory

WOOD-
LINE

SIBU | DESIGN
we decorate.



WL Carbonized Wood
2600 x 1000 / **NA** 20157 / **SA** 20224



2600 x 1000



WOOD-LINE

WL Carbonized Wood

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	impregnated paper	
Material thickness mm	1,3	1,43
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■□□	
Rolled packable **	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets***	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1


Special colors

–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Design sheets are to be rolled with the patterned side on the inside (applies for both the NA and SA versions). We recommend that not more than 3 sheets be rolled per carton (480 x 480 mm).
*** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).



□
WL Wenge Wood



WL Wenge Wood
2600 x 1000 / **NA** 19016 / **SA** 19027

WOOD-LINE

WL Wenge Wood

2600 x 1000



Product characteristics

	NA	SA
Base material	HIPS	
Surface material	impregnated paper	
Material thickness mm	1,2	1,33
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■□□□	
Rolled packable **	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Design sheets are to be rolled with the patterned side on the inside (applies for both the NA and SA versions). We recommend that not more than 3 sheets be rolled per carton (480 x 480 mm).



WL Maple Alpine
2600 x 1000 / **NA** 19018 / **SA** 19029



2600 x 1000



WOOD-LINE

WL Maple Alpine

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	impregnated paper	
Material thickness mm	1,3	1,43
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■□□	
Rolled packable **	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Design sheets are to be rolled with the patterned side on the inside (applies for both the NA and SA versions). We recommend that not more than 3 sheets be rolled per carton (480 x 480 mm).



□
WL Nutwood



WL Nutwood
2600 x 1000 / **NA** 19019 / **SA** 19030

WOOD-LINE

WL Nutwood

2600 x 1000



Product characteristics

	NA	SA
Base material	HIPS	
Surface material	impregnated paper	
Material thickness mm	1,3	1,43
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■□□	
Rolled packable **	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Design sheets are to be rolled with the patterned side on the inside (applies for both the NA and SA versions). We recommend that not more than 3 sheets be rolled per carton (480 x 480 mm).



WL Nutwood Country
2600 x 1000 / **NA** 19017 / **SA** 19028



2600 x 1000



WOOD-LINE

WL Nutwood Country

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	impregnated paper	
Material thickness mm	1,3	1,43
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■□□	
Rolled packable **	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Design sheets are to be rolled with the patterned side on the inside (applies for both the NA and SA versions). We recommend that not more than 3 sheets be rolled per carton (480 x 480 mm).



Photo: © Iuliia Nazarenko 123rf com



WL Sessile OAK
2600 x 1000 / **NA** 22786 / **SA** 22787



2600 x 1000



WOOD-LINE

WL Sessile OAK

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	impregnated paper	
Material thickness mm	1,3	1,43
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■□□	
Rolled packable **	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Design sheets are to be rolled with the patterned side on the inside (applies for both the NA and SA versions). We recommend that not more than 3 sheets be rolled per carton (480 x 480 mm).





WL OAK TREE Light
2600 x 1000 / **NA** 17278 / **SA** 17279

WOOD-LINE

WL OAK TREE Light

2600 x 1000



Product characteristics

	NA	SA
Base material	HIPS	
Surface material	impregnated paper	
Material thickness mm	1,2	1,33
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■□□□	
Rolled packable **	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.

** Design sheets are to be rolled with the patterned side on the inside (applies for both the NA and SA versions). We recommend that not more than 3 sheets be rolled per carton (480 x 480 mm).

DECO-
LINE

SIBU | DESIGN
we decorate.



DM OXIDIZED Silver AR
2600 x 1000 / **NA** 20139 / **SA** 20187



DM OXIDIZED Autumn AR
2600 x 1000 / **NA** 20143 / **SA** 20191



DM OXIDIZED Copper AR
2600 x 1000 / **NA** 20138 / **SA** 20186



DM OXIDIZED Nickel AR
2600 x 1000 / **NA** 20140 / **SA** 20188



DM OXIDIZED Platin AR
2600 x 1000 / **NA** 20141 / **SA** 20189



DM OXIDIZED Titan AR
2600 x 1000 / **NA** 20142 / **SA** 20190

2600 x 1000





DECO-LINE abrasion-resistant

DM OXIDIZED AR

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	Print	
Material thickness mm	1,0	1,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■■	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	–	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets *	✓	
PVA pre-treatment	✓	–

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A1

Special colors

–





DM SLIGHTLY USED Gold AR
2600 x 1000 / **NA** 20153 / **SA** 20201



DM SLIGHTLY USED Bronze AR
2600 x 1000 / **NA** 20152 / **SA** 20200



DM SLIGHTLY USED Copper AR
2600 x 1000 / **NA** 20151 / **SA** 20199



DM SLIGHTLY USED Titan AR
2600 x 1000 / **NA** 20154 / **SA** 20202

DECO-LINE abrasion-resistant

DM SLIGHTLY USED AR

2600 x 1000



Product characteristics

	NA	SA
Base material	HIPS	
Surface material	Print	
Material thickness mm	1,0	1,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■■	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	–	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets *	✓	
PVA pre-treatment	✓	–

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A1

Special colors

–



DM METALLIC USED Champagne AR
2600 x 1000 / **NA** 20150 / **SA** 20198



DM METALLIC USED Silver AR
2600 x 1000 / **NA** 20145 / **SA** 20193



DM METALLIC USED Titan AR
2600 x 1000 / **NA** 20144 / **SA** 20192



Photo: © istock.com

2600 x 1000



DECO-LINE abrasion-resistant

DM METALLIC USED AR

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	Print	
Material thickness mm	1,0	1,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■■	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	–	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets *	✓	
PVA pre-treatment	✓	–

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A1

Special colors

–





DM METALLIC USED Ivory AR
2600 x 1000 / **NA** 20149 / **SA** 20197



DM METALLIC USED Sand AR
2600 x 1000 / **NA** 20147 / **SA** 20195



DM METALLIC USED Bronze AR
2600 x 1000 / **NA** 20146 / **SA** 20194



DM METALLIC USED Steel AR
2600 x 1000 / **NA** 20148 / **SA** 20196

DECO-LINE abrasion-resistant

DM METALLIC USED AR

2600 x 1000



Product characteristics

	NA	SA
Base material	HIPS	
Surface material	Print	
Material thickness mm	1,0	1,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■■	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	–	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets *	✓	
PVA pre-treatment	✓	–

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A1

Special colors

–




DM REFINED METAL Silver AR
2600 x 1000 / **NA** 20155 / **SA** 20203



DM REFINED METAL Titan AR
2600 x 1000 / **NA** 20156 / **SA** 20204



2600 x 1000



DECO-LINE abrasion-resistant

DM REFINED METAL AR

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	Print	
Material thickness mm	1,0	1,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■■	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	–	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets *	✓	
PVA pre-treatment	✓	–

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A1

Special colors

–






DM SILENT Gold AR
2600 x 1000 / **NA** 19200 / **SA** 19208

DECO-LINE abrasion-resistant

DM SILENT Gold AR

2600 x 1000



Product characteristics

	NA	SA
Base material	HIPS	
Surface material	Print	
Material thickness mm	1,0	1,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■■	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	–	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets *	✓	
PVA pre-treatment	✓	–

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A1

Special colors

–



DM Iron Age AR
2600 x 1000 / **NA** 19201 / **SA** 19209



2600 x 1000



DECO-LINE abrasion-resistant

DM Iron Age AR

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	Print	
Material thickness mm	1,0	1,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■■	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	–	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets *	✓	
PVA pre-treatment	✓	–

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A1

Special colors

–



□
DM CLASSY Silver AR

Photo: © fotolia.com

DECO-LINE abrasion-resistant

DM CLASSY AR

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	Print	
Material thickness mm	1,0	1,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■■	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	–	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets *	✓	
PVA pre-treatment	✓	–

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A1

Special colors

–



DM CLASSY Silver AR
2600 x 1000 / **NA** 19326 / **SA** 19337



DM CLASSY Bronze AR
2600 x 1000 / **NA** 19011 / **SA** 19022



DM CLASSY Copper AR
2600 x 1000 / **NA** 19199 / **SA** 19207



DM CLASSY Gold AR
2600 x 1000 / **NA** 19010 / **SA** 19021



DM CLASSY Black AR
2600 x 1000 / **NA** 19325 / **SA** 19336

2600 x 1000





DM LUXURY Bronze AR
2600 x 1000 / **NA** 21487 / **SA** 21488



DM LUXURY Gold AR
2600 x 1000 / **NA** 21391 / **SA** 21392



□
DM LUXURY Bronze AR

2600 x 1000



DECO-LINE

DM LUXURY AR

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	Print	
Material thickness mm	1,0	1,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■■	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	–	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–



□
DM VINTAGE Copper



DM VINTAGE Copper
2600 x 1000 / **NA** 17276 / **SA** 17277



DM VINTAGE Silver
2600 x 1000 / **NA** 17274 / **SA** 17275

DECO-LINE

DM Vintage

2600 x 1000



Product characteristics

	NA	SA
Base material	HIPS	
Surface material	Print	
Material thickness mm	1,0	1,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■□	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–



DM CONCRETE Grey
2600 x 1000 / **NA** 22827 / **SA** 22828



2600 x 1000



DECO-LINE

DM CONCRET Grey

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PP	
Material thickness mm	1,3	1,43
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■■	
Rolled packable **	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets ***	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–

** Design sheets to be rolled with the decor side outwardly (both – NA and SA version). We recommend rolling not more than 3 sheets per carton (480 x 480 mm).
*** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).



□
DM MONSOON VINTAGE Brown

Photo: © Berni - fotolia.com



DM MONSOON VINTAGE Brown
2600 x 1000 / **NA** 17033 / **SA** 17037

DECO-LINE

DM MONSOON

2600 x 1000



Product characteristics

	NA	SA
Base material	HIPS	
Surface material	Print	
Material thickness mm	1,0	1,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■□□□	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	–	–
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–




DM CEMENT Light
2600 x 1000 / **NA** 19087 / **SA** 19091



□
DM CEMENT Light

2600 x 1000



DECO-LINE

DM CEMENT Light

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	impregnated paper	
Material thickness mm	1,2	1,33
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■□	
Rolled packable **	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets ***	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Design sheets are to be rolled with the patterned side on the inside (applies for both the NA and SA versions). We recommend that not more than 3 sheets be rolled per carton (480 x 480 mm).
*** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).





DM CEMENT Dark
2600 x 1000 / **NA** 19088 / **SA** 19092

DECO-LINE

DM CEMENT Dark

2600 x 1000



Product characteristics

	NA	SA
Base material	HIPS	
Surface material	impregnated paper	
Material thickness mm	1,3	1,43
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■□□	
Rolled packable **	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets ***	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Design sheets are to be rolled with the patterned side on the inside (applies for both the NA and SA versions). We recommend that not more than 3 sheets be rolled per carton (480 x 480 mm).
*** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).



DM MARBLE White
2600 x 1000 / **NA** 19327 / **SA** 19338



□
DM MARBLE White

Photo: © fotolia.com

2600 x 1000



DECO-LINE

DM MARBLE White

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	impregnated paper	
Material thickness mm	1,3	1,43
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■□	
Rolled packable **	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets ***	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–

SIBU | DESIGN we decorate. \ 92

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Design sheets are to be rolled with the patterned side on the inside (applies for both the NA and SA versions). We recommend that not more than 3 sheets be rolled per carton (480 x 480 mm).
*** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).



□
DM Travertin



DM Travertin
2600 x 1000 / **NA** 19328 / **SA** 19339

DECO-LINE

DM Travertin

2600 x 1000



Product characteristics

	NA	SA
Base material	HIPS	
Surface material	impregnated paper	
Material thickness mm	1,3	1,43
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■□□	
Rolled packable **	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets***	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Design sheets are to be rolled with the patterned side on the inside (applies for both the NA and SA versions). We recommend that not more than 3 sheets be rolled per carton (480 x 480 mm).
*** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).



DM GENSIS Grey supermatt AR
2600 x 1000 / **NA** 23093 / **SA** 23101



□
DM GENESIS Grey supermatt AR

2600 x 1000



DECO-LINE

DM GENESIS Grey supermatt AR

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PET	
Material thickness mm	1,4	1,53
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■□	
Rolled packable **	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets ***	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Design sheets are to be rolled with the patterned side on the inside (applies for both the NA and SA versions). We recommend that not more than 3 sheets be rolled per carton (480 x 480 mm).
*** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).



□
DM GENESIS White supermatt AR

Photo: © iStock.com



DM GENSIS White supermatt AR
2600 x 1000 / **NA** 23092 / **SA** 23100

DECO-LINE

DM GENESIS White supermatt AR

2600 x 1000



Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PET	
Material thickness mm	1,4	1,53
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■□	
Rolled packable **	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets ***	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Design sheets are to be rolled with the patterned side on the inside (applies for both the NA and SA versions). We recommend that not more than 3 sheets be rolled per carton (480 x 480 mm).
*** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).



DM MARBLE White supermatt AR
2600 x 1000 / **NA** 23091 / **SA** 23098



□
DM MARBLE White supermatt AR

Photo: © iStock.com

DECO-LINE

DM MARBLE White supermatt AR

2600 x 1000



Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PET	
Material thickness mm	1,4	1,53
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■□	
Rolled packable **	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets ***	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Design sheets are to be rolled with the patterned side on the inside (applies for both the NA and SA versions). We recommend that not more than 3 sheets be rolled per carton (480 x 480 mm).
*** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).



DM MARBLE Black supermatt AR

Photo: © iStock.com



DM MARBLE Black supermatt AR
2600 x 1000 / **NA** 22947 / **SA** 23099

DECO-LINE

DM MARBLE Black supermatt AR

2600 x 1000



Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PET	
Material thickness mm	1,4	1,53
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■□□	
Rolled packable **	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets ***	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Design sheets are to be rolled with the patterned side on the inside (applies for both the NA and SA versions). We recommend that not more than 3 sheets be rolled per carton (480 x 480 mm).
*** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).



DM Magic White AR
2600 x 1000 / 1 mm / **NA** 15414 / **SA** 15422



DM Magic Black AR
2600 x 1000 / 1 mm / **NA** 15415 / **SA** 15423
2600 x 1000 / 2 mm / **NA** 15417 / **SA** -



DECO-LINE abrasion-resistant

DM Magic AR

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PET	
Material thickness mm	1,0 / 2,0	1,13 / 2,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Abrasion resistance	■■■■■■	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

On request



□
DM Graphit Black matt AR

Photo: Fotolia.com



DM Snow White matt AR
2600 x 1000 / **NA** 23145 / **SA** 23146



DM Graphite Black matt AR
2600 x 1000 / **NA** 23144 / **SA** 23147

DECO-LINE abrasion-resistant

DM matt AR

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PET	
Material thickness mm	1,0	1,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Abrasion resistance	■■■■■□	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

On request


* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.



DM GALAXY Silver
2600 x 1000 / **NA** 10169 / **SA** 10175



2600 x 1000



DECO-LINE

DM GALAXY

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	Print	
Material thickness mm	1,0	1,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■□	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–





DM Hollywood
2600 x 1000 / **NA** 18433 / **SA** 18442



DM Hollywood Blue
2600 x 1000 / **NA** 20945 / **SA** 21272



DM Aqua
2600 x 1000 / **NA** 18424 / **SA** 18443

DECO-LINE

DM Mirror

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PET	
Material thickness mm	1,0	1,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■□□	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment


	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

On request



DM LUXURY Holografico
2600 x 1000 / **NA** 19009 / **SA** 19020



2600 x 1000



DECO-LINE

DM LUXURY Holografico

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	Print	
Material thickness mm	1,0	1,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■□□□□□	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets *	✓	
PVA pre-treatment	✓	–

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A1

Special colors

–



□
DM Smoke PF



FR
PR+

DM Silver PF
2600 x 1000 / **NA** 10357 / **SA** 10363



FR
PR+

DM Smoke PF
2600 x 1000 / **NA** 10385 / **SA** 10389

DECO-LINE abrasion-resistant

DM PF

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	Print	
Material thickness mm	1,0	1,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Abrasion resistance	■■■■■■	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors


On request



DM OPTICAL MIRROR Silver AR
2800 x 1250 / **NA** 20877



DM OPTICAL MIRROR Fashion Grey AR
2800 x 1250 / **NA** 21244



DM OPTICAL MIRROR Anthracite AR
2800 x 1250 / **NA** 21241



DM OPTICAL MIRROR Brass AR
2800 x 1250 / **NA** 21242



DM OPTICAL MIRROR Gold AR
2800 x 1250 / **NA** 21243



DM OPTICAL MIRROR Copper AR
2800 x 1250 / **NA** 21245



□
DM OPTICAL
MIRROR Silver AR

DECO-LINE abrasion-resistant

DM OPTICAL MIRROR AR

Product characteristics

	NA
Base material	HIPS
Surface material	PET
Material thickness mm	1,0
Temperature stability	up to 60 °C
Wet room suitability	■■■□
Abrasion resistance	■■■■■■
Rolled packable	✓

Processing

	NA
Cutting, punching	✓
Drilling	✓
Sawing, milling	✓
Laser cutting	✓
Hot bending	✓
Thermoforming	–
PVA compressible	✓
Smallest bending radius	150 mm

Extra equipment

	NA
Special formats	On request
Further thicknesses	✓
Cuttings	✓
Magnetic from 3 sheets	–
PVA pre-treatment	✓

Accessories

SIBUKLE	–

Special colors

–



DM Gold MMS



DM Silver MMS
2600 x 1000 / **NA** 20499 / **SA** 20501



DM Gold MMS
2600 x 1000 / **NA** 20500 / **SA** 20502

DECO-LINE

DM MMS

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	Print	
Material thickness mm	1,0	1,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■□□□	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

On request



DM Silver
2600 x 1000 / 1 mm / **NA** 10312 / **SA** 10324
2000 x 1000 / 1 mm / **NA** 10304 / **SA** 10322
2000 x 1000 / 2 mm / **NA** 12114 / **SA** 10323



DM Silver/White
2000 x 1000 / 1 mm / **NA** 10372 / **SA** 10381



DECO-LINE

DM Mirror

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PET	
Material thickness mm	1,0 / 2,0	1,13 / 2,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■□□	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

On request



□
DM Gold AR



DM Gold AR
2600 x 1000 / **NA** 10181 / **SA** 10187
2000 x 1000 / **NA** 10178 / **SA** 10186



DM Rosegold AR
2600 x 1000 / **NA** 20955 / **SA** 20956



DM Brass AR
2600 x 1000 / **NA** 10135 / **SA** 10139

DECO-LINE **abrasion-resistant**

DM Mirror AR

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PET	
Material thickness mm	1,0	1,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■■	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–



DM Anthracite AR
2600 x 1000 / **NA** 10120 / **SA** 10125



DM Brown AR
2600 x 1000 / **NA** 10147 / **SA** 10150



DM Rose AR
2600 x 1000 / **NA** 10271 / **SA** 12428



DM Iceblue AR
2600 x 1000 / **NA** 10204 / **SA** 10210



DM Fashion Grey AR
2600 x 1000 / **NA** 13808 / **SA** 13810



DECO-LINE abrasion-resistant

DM Mirror AR

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PET	
Material thickness mm	1,0	1,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■■	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment


	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–



□
DM Fashion Red (printed)

Photo: © Form Factory



DM Bronze
2600 x 1000 / **NA** 10143 / **SA** 15275



DM Champagne
2600 x 1000 / **NA** 12416 / **SA** 12430



DM Gold 30
2600 x 1000 / **NA** 10222/ **SA** 11504



DM Fashion Red
2600 x 1000 / **NA** 10213 / **SA** 13807

DECO-LINE

DM Mirror

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PET	
Material thickness mm	1,0	1,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■□□	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–



DM Brass brushed matt AR
2600 x 1000 / **NA** 15290 / **SA** 15298



DM Gold brushed matt AR
2600 x 1000 / **NA** 15291 / **SA** 15299



□
DM Gold
brushed matt AR

DECO-LINE **abrasion-resistant**

DM Brushed matt

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PET	
Material thickness mm	1,0	1,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■■	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–

2600 x 1000





□
DM Silver brushed

DECO-LINE abrasion-resistant

DM Brushed

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PET	
Material thickness mm	1,0	1,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■■	
Abrasion resistance DM Silver brushed	■■■■■□	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors

–



DM Silver brushed
2600 x 1000 / **NA** 10291 / **SA** 10298
2000 x 1000 / **NA** 10286 / **SA** 10296



DM HGS
2600 x 1000 / **NA** 10193 / **SA** 10199



DM Champagne brushed
2600 x 1000 / **NA** 12417 / **SA** 12433



DM Titan brushed
2600 x 1000 / **NA** 12285 / **SA** 12431



DM Copper brushed
2600 x 1000 / **NA** 12418 / **SA** 12432

2600 x 1000





DM DEEP BRUSHED Gravel
2600 x 1000 / **NA** 22822 / **SA** 22823



DM DEEP BRUSHED Sandy
2600 x 1000 / **NA** 22825 / **SA** 22824



□
DM DEEP BRUSHED Gravel

Photo: © iStock.com

2600 x 1000



DECO-LINE

DM DEEP BRUSHED

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PP	
Material thickness mm	1,3	1,43
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■■	
Rolled packable **	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
Thermoforming	–	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	✓	✓
Cuttings	✓	✓
Magnetic from 3 sheets ***	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A1

Special colors


–

** Design sheets to be rolled with the decor side outwardly (both – NA and SA version). We recommend rolling not more than 3 sheets per carton (480 x 480 mm).
*** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).




MULTISTYLE

SIBU | DESIGN
we decorate.



MS 3x3 flex Classic Silver
980 x 980 / **SA** 10650



MS 3x3 flex Classic Gold AR
980 x 980 / **SA** 10592



□
MS 3x3 flex Classic Gold AR

MULTISTYLE

MS 3x3

Product characteristics

	SA
Base material	HIPS
Surface material	PET
Material thickness mm	1,2
Temperature stability	up to 50 °C
Wet room suitability	■■■□
Abrasion resistance	■■■■□□
Abrasion resistance MS Gold AR	■■■■■■
Rolled packable	✓

Processing

	SA
Cutting, punching	✓
Drilling	✓
Sawing, milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	–

Extra equipment

	SA
Special formats	–
Further thicknesses	–
Cuttings	✓
Magnetic from 3 sheets	✓
PVA pre-treatment	–


Accessories

SIBUKLE	Spatula A1


Special colors

On request






MS 5x5 flex Classic Hollywood
980 x 980 / **SA** 18436



MS 5x5 flex Classic Silver
980 x 980 / **SA** 10657



MS 5x5 flex Classic Gold AR
980 x 980 / **SA** 10598

MULTISTYLE

MS 5x5

Product characteristics

	SA
Base material	HIPS
Surface material	PET
Material thickness mm	1,2
Temperature stability	up to 50 °C
Wet room suitability	■■■□
Abrasion resistance	■■■■□□
Abrasion resistance MS Gold AR	■■■■■■
Rolled packable	✓

Processing

	SA
Cutting, punching	✓
Drilling	✓
Sawing, milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	–

Extra equipment

	SA
Special formats	✓
Maximum length mm	3000
Maximum width mm	1000
Further thicknesses	–
Cuttings	✓
Magnetic from 3 sheets	✓
PVA pre-treatment	–

Accessories

SIBUKLE	Spatula A1

Special colors

On request



MS 5x5 flex Classic GALAXY Silver
980 x 980 / **SA** 10575



□
MS 5x5 flex Classic GALAXY Silver

MULTISTYLE

MS 5x5

Product characteristics

	SA
Base material	HIPS
Surface material	Print
Material thickness mm	1,2
Temperature stability	up to 50 °C
Wet room suitability	■■■□
Abrasion resistance	■■■■■□
Rolled packable	✓

Processing

	SA
Cutting, punching	✓
Drilling	✓
Sawing, milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	–

Extra equipment


	SA
Special formats	✓
Maximum length mm	3000
Maximum width mm	1000
Further thicknesses	–
Cuttings	✓
Magnetic from 3 sheets	✓
PVA pre-treatment	–

Accessories


SIBUKLE	Spatula A1

Special colors


–



□
MS 5x5 flex Classic MAGIC Black



MS 5x5 flex Classic MAGIC White
980 x 980 / **SA** 13476



MS 5x5 flex Classic MAGIC Black
980 x 980 / **SA** 13475

MULTISTYLE

MS 5x5

Product characteristics

	SA
Base material	HIPS
Surface material	PET
Material thickness mm	1,2
Temperature stability	up to 50 °C
Wet room suitability	■■■■
Abrasion resistance	■■■■□□
Rolled packable	✓

Processing

	SA
Cutting, punching	✓
Drilling	✓
Sawing, milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	–

Extra equipment

	SA
Special formats	✓
Maximum length mm	3000
Maximum width mm	1000
Further thicknesses	–
Cuttings	✓
Magnetic from 3 sheets	✓
PVA pre-treatment	–
Abrasion resistance	■■■■■■

Accessories


SIBUKLE	Spatula A1

Special colors


On request



MS 10x10 flex Classic Silver
980 x 980 / **SA** 10639



MS 10x10 flex Classic Gold AR
980 x 980 / **SA** 10581



MS 20x20 flex Classic Silver
980 x 980 / **SA** 10644



MS 20x20 flex Classic Gold AR
980 x 980 / **SA** 10582



MULTISTYLE

MS 10x10 / 20x20

Product characteristics

	SA
Base material	HIPS
Surface material	PET
Material thickness mm	1,2
Temperature stability	up to 50 °C
Wet room suitability	■■■□
Abrasion resistance	■■■■□□
Abrasion resistance MS Gold AR	■■■■■■
Rolled packable	✓

Processing

	SA
Cutting, punching	✓
Drilling	✓
Sawing, milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	–

Extra equipment

	SA
Special formats	✓
Maximum length mm	3000
Maximum width mm	1000
Further thicknesses	–
Cuttings	✓
Magnetic from 3 sheets	✓
PVA pre-treatment	–

Accessories

SIBUKLE	Spatula A1


Special colors

On request





MSC 10x10 flex Classic Silver
2600 x 1000 / **SA** 14239



MSC 30x30 flex Classic Silver
2600 x 1000 / **SA** 14279

MULTISTYLE

MSC 10x10 / 30x30

Product characteristics

	SA
Base material	HIPS
Surface material	PET
Material thickness mm	1,2
Temperature stability	up to 50 °C
Wet room suitability	■■■□
Abrasion resistance	■■■■□□
Rolled packable	✓

Processing

	SA
Cutting, punching	✓
Drilling	✓
Sawing, milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	–

Extra equipment

	SA
Special formats	✓
Maximum length mm	3000
Maximum width mm	1000
Further thicknesses	–
Cuttings	✓
Magnetic from 3 sheets	✓
PVA pre-treatment	–


Accessories

SIBUKLE	Spatula A1

Special colors

On request

2600 x 1000



STRUCTURE-
LINE

SIBU | DESIGN
we decorate.



SL CRASHED OLD Platin
2600 x 1000 / **NA** 19519 / **SA** 19523



2600 x 1000



STRUCTURE-LINE

SL CRASHED OLD Platin

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	Print	
Material thickness mm	1,0	1,13
Max. relief height mm	2,8	3,04
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■□	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	–	–
Further thicknesses	–	–
Cuttings	✓	✓
Magnetic from 3 sheets *	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A2

Special colors

On request

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).



□
SL CRASHED Silver

Photo: © fotolia.com



SL CRASHED Silver
2600 x 1000 / **NA** 19335 / **SA** 19346

STRUCTURE-LINE

SL CRASHED

2600 x 1000



Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PET	
Material thickness mm	1,0	1,13
Max. relief height mm	2,4	2,64
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■□□	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	–	
Further thicknesses	–	–
Cuttings	✓	✓
Magnetic from 3 sheets *	✓	
PVA pre-treatment	✓	–

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A2

Special colors


On request



SL IMPACT VINTAGE Silver
2600 x 1000 / **NA** 17230 / **SA** 17231



SL IMPACT ANTIQUE Bronze
2600 x 1000 / **NA** 17232 / **SA** 17233



2600 x 1000



STRUCTURE-LINE

SL IMPACT

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	Print	
Material thickness mm	1,0	1,13
Max. relief height mm	1,6	1,73
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■□	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	–	–
Further thicknesses	–	–
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories


SIBUKLE	Spatula A2

Special colors

On request



SL IMPACT VINTAGE Silver



SL LAVA VINTAGE Copper
2600 x 1000 / **NA** 14786 / **SA** 14805



2600 x 1000



STRUCTURE-LINE

SL LAVA

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	Print	
Material thickness mm	1,0	1,25
Max. relief height mm	2,1	2,35
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■□	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	–	–
Further thicknesses	–	–
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A2


Special colors

On request



□
SL RACE
VINTAGE Copper/Silver

Photo Wilhelm Radinger



SL RACE VINTAGE Silver/Bronze
2600 x 1000 / **NA** 17242 / **SA** 17243



SL RACE VINTAGE Copper/Silver
2600 x 1000 / **NA** 17240 / **SA** 17241

STRUCTURE-LINE

SL RACE

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	Print	
Material thickness mm	1,0	1,13
Max. relief height mm	1,7	1,83
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■□□□	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	–	–
Further thicknesses	–	–
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A2

Special colors


On request

2600 x 1000






SL CROCO Silver PF/Silver
2600 x 1000 / **NA** 13410 / **SA** 13520



SL CROCO Smoke PF/Silver
2600 x 1000 / **NA** 13411 / **SA** 13521



2600 x 1000



STRUCTURE-LINE

SL CROCO

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	Print	
Material thickness mm	1,0	1,25
Max. relief height mm	2,6	2,85
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■□□	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	–	–
Further thicknesses	–	–
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓ *	–

Accessories

SIBUKLE	Spatula A2

Special colors

On request

* except Smoke PF met



□
SL SQUARE 3 HGS




SL SQUARE 3 HGS
2600 x 1000 / 1,7 mm / **NA** 11272 / **SA** 11273

STRUCTURE-LINE

SL SQUARE 3

2600 x 1000



Product characteristics

	NA	SA
Base material	HIPS	
Surface material	PET	
Material thickness mm	1,0	1,13
Max. relief height mm	1,7 / 2,0	1,83 / 2,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■■	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	–	
Further thicknesses	–	–
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A2

Special colors

On request

ACRYLIC-
LINE

SIBU | DESIGN
we decorate.

AC MOTION ONE White
2600 x 1000 / **NA** 15933 / **SA** 15953



AC MOTION ONE Black
2600 x 1000 / **NA** 15936 / **SA** 15956



□
AC MOTION ONE Black

2600 x 1000



ACRYLIC-LINE abrasion-resistant

AC MOTION ONE

Product characteristics

	NA	SA
Base material	ABS	
Surface material	PMMA	
Material thickness mm	0,7	0,83
Max. relief height mm	1,1	1,23
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Abrasion resistance	■■■■■□	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	–	–
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–

Accessories

SIBUKLE	Spatula A2
Politur-Kit	available
Farbgleiche Kanten	available


Special colors

On request



Photo: GARANTküche

AC MOTION TWO White
2600 x 1000 / **NA** 15755 / **SA** 15764



AC MOTION TWO Black
2600 x 1000 / **NA** 15754 / **SA** 15763

ACRYLIC-LINE abrasion-resistant

AC MOTION TWO

Product characteristics

	NA	SA
Base material	ABS	
Surface material	PMMA	
Material thickness mm	0,7	0,83
Max. relief height mm	1,1	1,23
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Abrasion resistance	■■■■■□	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	✓	–
Smallest bending radius	150 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	–	–
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	✓	–


Accessories

SIBUKLE	Spatula A2
Politur-Kit	available
Farbgleiche Kanten	available

Special colors

On request

2600 x 1000



TRANSLUCENT-
LINE

SIBU | DESIGN
we decorate.



TL LINEA 104x62 OLD Platin
2600 x 1000 / **NA** 18434 / **SA** 18607



TL LINEA 104x62 SILENT Gold AR
2600 x 1000 / **NA** 22031 / **SA** 22033



□
TL LINEA 104 x 62 SILENT Gold AR

Photo: Ariadna de Raadt

2600 x 1000



TRANSLUCENT-LINE

TL LINEA

Product characteristics

	NA	SA
Base material	HIPS	
Surface material	Print	
Material thickness mm	1,5	1,63
Temperature stability	up to 60 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■■	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	–	–
PVA compressible	–	–
Smallest bending radius	240 mm	

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	–	–
Cuttings	✓	✓
Magnetic	–	
PVA pre-treatment	–	–

Accessories

SIBUKLE	–

Special colors

On request




TL LINEA
104 x 62 OLD Platin

PUNCH-
LINE / 3D

SIBU | DESIGN
we decorate.



PL3D Q-10-30 OLD Platin/Silver
2600 x 1000 / **NA** 17833 / **SA** 17857



□
PL3D Q-10-30
OLD Platin/Silver

2600 x 1000



PUNCH-LINE / 3D

PL3D Q-10-30

Product characteristics

	NA	SA
Base material	APET, HIPS	
Surface material	Print	
Material thickness mm	1,3	1,43
Temperature stability	up to 50 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■□	
Rolled packable *	✓	✓

* Design sheets are to be rolled with the patterned side on the inside (applies for both the NA and SA versions). We recommend that not more than 3 sheets be rolled per carton (480 x 480 mm). (Up to 40° C)
** Up to 40° C

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	–	–
Smallest bending radius **	300 mm	300 mm

Extra equipment

	NA	SA
Special formats	–	–
Further thicknesses	–	–
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	–	–

Accessories

SIBUKLE	–

Special colors

On request



□
PL3D H-10-30
Pearl White PF/Gold




PL3D H-10-30 Pearl White PF/Gold
2600 x 1000 / **NA** 17832 / **SA** 17856

PUNCH-LINE / 3D

PL3D H-10-30

2600 x 1000



Product characteristics

	NA	SA
Base material	APET, HIPS	
Surface material	Print	
Material thickness mm	1,3	1,43
Temperature stability	up to 50 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■■	
Rolled packable *	✓	✓

* Design sheets are to be rolled with the patterned side on the inside (applies for both the NA and SA versions). We recommend that not more than 3 sheets be rolled per carton (480 x 480 mm). (Up to 40° C)
** Up to 40° C

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	–	–
Smallest bending radius **	300 mm	300 mm

Extra equipment

	NA	SA
Special formats	–	–
Further thicknesses	–	–
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	–	–

Accessories

SIBUKLE	–

Special colors

On request



PL3D ROSES Pearl White PF/Gold
2600 x 1000 / **NA** 16443 / **SA** 16444



PL3D ROSES Silver PF/Silver
2600 x 1000 / **NA** 13917 / **SA** 13919



2600 x 1000



PUNCH-LINE / 3D

PL3D ROSES

Product characteristics

	NA	SA
Base material	APET / HIPS	
Surface material	Print	
Material thickness mm	1,3	1,43
Temperature stability	up to 50 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■■	
Rolled packable *	✓	✓

* Design sheets are to be rolled with the patterned side on the inside (applies for both the NA and SA versions). We recommend that not more than 3 sheets be rolled per carton (480 x 480 mm). (Up to 40° C)
** Up to 40° C

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	–	–
PVA compressible	–	–
Smallest bending radius **	300 mm	300 mm

Extra equipment

	NA	SA
Special formats	–	–
Further thicknesses	–	–
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	–	–

Accessories

SIBUKLE	–

Special colors


On request



□
PL3D Q 10-40-40 Silver PF/Silver



PL3D Q 10-40-40 Silver PF/Silver
2600 x 1000 / **NA** 10052 / **SA** 10053



PL3D Q 10-40-40 Smoke PF T1/Silver matt
2600 x 1000 / **NA** 12519 / **SA** 12557

PUNCH-LINE / 3D

PL3D Q 10-40-40

Product characteristics

	NA	SA
Base material	APET / HIPS	
Surface material	Print	
Material thickness mm	1,3	1,43
Temperature stability	up to 50 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■■	
Rolled packable *	✓	✓

* Design sheets are to be rolled with the patterned side on the inside (applies for both the NA and SA versions). We recommend that not more than 3 sheets be rolled per carton (480 x 480 mm). (Up to 40° C)
** Up to 40° C

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	–	–
Smallest bending radius **	300 mm	300 mm

Extra equipment

	NA	SA
Special formats	–	–
Further thicknesses	–	–
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	–	–


Accessories

SIBUKLE	–

Special colors

On request

2600 x 1000






PL3D Q 5-15-15 Black T1/Silver
2600 x 1000 / **NA** 12384 / **SA** 12549



2600 x 1000



PUNCH-LINE / 3D

PL3D Q 5-15-15

Product characteristics

	NA	SA
Base material	APET / HIPS	
Surface material	Print	
Material thickness mm	1,3	1,43
Temperature stability	up to 50 °C	
Wet room suitability	■■■□	
Abrasion resistance	■■■■■■	
Rolled packable *	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	–	–
Smallest bending radius **	300 mm	300 mm

* Design sheets are to be rolled with the patterned side on the inside (applies for both the NA and SA versions). We recommend that not more than 3 sheets be rolled per carton (480 x 480 mm). (Up to 40° C)
** Up to 40° C

Extra equipment

	NA	SA
Special formats	–	–
Further thicknesses	–	–
Cuttings	✓	✓
Magnetic from 3 sheets	✓	
PVA pre-treatment	–	–


Accessories

SIBUKLE	–

Special colors

On request






PL Q 5-15-15 Silver PF
2600 x 1000 / **NA** 10986 / **SA** 10988

PUNCH-LINE

PL Q 5-15-15

2600 x 1000



Product characteristics

	NA	SA
Base material	HIPS	
Surface material	Print	
Material thickness mm	1,0	1,13
Temperature stability	up to 60 °C	
Wet room suitability	■■■■	
Abrasion resistance	■■■■■■	
Rolled packable	✓	✓

Processing

	NA	SA
Cutting, punching	✓	✓
Drilling	✓	✓
Sawing, milling	✓	–
Laser cutting	✓	✓
Hot bending	✓	–
PVA compressible	–	–
Smallest bending radius	150 mm	150 mm

Extra equipment

	NA	SA
Special formats	On request	
Further thicknesses	up to 2 mm	
Cuttings	✓	✓
Magnetic	–	
PVA pre-treatment	–	–

Accessories

SIBUKLE	–

Special colors

On request

ANTIGRAV

SIBU | DESIGN
we decorate.



FL CREPA VELVET Avocado Antigrav
2613 x 1005 / **NA** 22735



FL CREPA VELVET Volcano Antigrav
2613 x 1005 / **NA** 22736

Please consider the nap direction of the surface before further processing or product installation. If design panels are not installed in the same direction, there will be a visual color difference.


FL CREPA VELVET Avocado Antigrav

Photo: © istock.com

2613 x 1005



FABRIC-LINE

POSITIVE ACOUSTIC EFFECT

FL CREPA VELVET Antigrav

Product characteristics

	NA
Base material	PP-glass fibres
Surface material	PET fibres
Material thickness mm	3,9
Max. relief height mm	6
Temperature stability	up to 60 °C
Wet room suitability	■■■■
Rolled packable	–

Processing

	NA
Cutting, punching	✓
Drilling	✓
Sawing	✓
Milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	✓
Smallest bending radius	1000 mm

Extra equipment

	NA
Special formats	On request
Cuttings	✓
Magnetic from 3 sheets *	✓
PVA pre-treatment	–

Accessories

SIBUKLE	Spatula A2

Special colors

On request

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).




FL LAVA VELVET Volcano Antigrav

Photo © istock.com



FL LAVA VELVET Coal Antigrav
2613 x 1005 / **NA** 22737



FL LAVA VELVET Volcano Antigrav
2613 x 1005 / **NA** 22738


Please consider the nap direction of the surface before further processing or product installation. If design panels are not installed in the same direction, there will be a visual color difference.

FABRIC-LINE

POSITIVE ACOUSTIC EFFECT

FL LAVA VELVET Antigrav

2613 x 1005



Product characteristics

	NA
Base material	PP-glass fibres
Surface material	PET fibres
Material thickness mm	3,9
Max. relief height mm	6
Temperature stability	up to 60 °C
Wet room suitability	■■■■
Rolled packable	–

Processing

	NA
Cutting, punching	✓
Drilling	✓
Sawing	✓
Milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	✓
Smallest bending radius	1000 mm

Extra equipment

	NA
Special formats	On request
Cuttings	✓
Magnetic from 3 sheets *	✓
PVA pre-treatment	–

Accessories

SIBUKLE	Spatula A2

Special colors

On request

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).



FL COMB VELVET Curry Antigrav
2613 x 1005 / **NA** 22731



FL COMB VELVET Pearl Antigrav
2613 x 1005 / **NA** 22732

Please consider the nap direction of the surface before further processing or product installation. If design panels are not installed in the same direction, there will be a visual color difference.


FL COMB VELVET Curry Antigrav

Photo: © istock.com

FABRIC-LINE POSITIVE ACOUSTIC EFFECT

FL COMB VELVET Antigrav

2613 x 1005



Product characteristics

	NA
Base material	PP-glass fibres
Surface material	PET fibres
Material thickness mm	3,9
Max. relief height mm	6
Temperature stability	up to 60 °C
Wet room suitability	■■■■
Rolled packable	–

Processing

	NA
Cutting, punching	✓
Drilling	✓
Sawing	✓
Milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	✓
Smallest bending radius	1000 mm

Extra equipment

	NA
Special formats	On request
Cuttings	✓
Magnetic from 3 sheets *	✓
PVA pre-treatment	–


Accessories

SIBUKLE	Spatula A2

Special colors


On request

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).



FL SQUARE 2 VELVET Mocha Antigrav

Photo: © istock.com



FL SQUARE 2 VELVET Mocha Antigrav
2613 x 1005 / **NA** 22733



FL SQUARE 2 VELVET Coal Antigrav
2613 x 1005 / **NA** 22734

Please consider the nap direction of the surface before further processing or product installation. If design panels are not installed in the same direction, there will be a visual color difference.

FABRIC-LINE

POSITIVE ACOUSTIC EFFECT

FL SQUARE 2 VELVET Antigrav

Product characteristics

	NA
Base material	PP-glass fibres
Surface material	PET fibres
Material thickness mm	3,9
Max. relief height mm	6
Temperature stability	up to 60 °C
Wet room suitability	■■■■
Rolled packable	–

Processing

	NA
Cutting, punching	✓
Drilling	✓
Sawing	✓
Milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	✓
Smallest bending radius	1000 mm

Extra equipment

	NA
Special formats	On request
Cuttings	✓
Magnetic from 3 sheets *	✓
PVA pre-treatment	–

Accessories


SIBUKLE	Spatula A2

Special colors

On request

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

2613 x 1005





FL CUBE VELVET Bordeaux Antigrav
2613 x 1005 / **NA** 22739



FL CUBE VELVET Pearl Antigrav
2613 x 1005 / **NA** 22740

Please consider the nap direction of the surface before further processing or product installation. If design panels are not installed in the same direction, there will be a visual color difference.



2613 x 1005



FABRIC-LINE POSITIVE ACOUSTIC EFFECT

FL CUBE VELVET Antigrav

Product characteristics

	NA
Base material	PP-glass fibres
Surface material	PET fibres
Material thickness mm	3,9
Max. relief height mm	6
Temperature stability	up to 60 °C
Wet room suitability	■■■■
Rolled packable	–

Processing

	NA
Cutting, punching	✓
Drilling	✓
Sawing	✓
Milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	✓
Smallest bending radius	1000 mm

Extra equipment

	NA
Special formats	On request
Cuttings	✓
Magnetic from 3 sheets *	✓
PVA pre-treatment	–

Accessories

SIBUKLE	Spatula A2

Special colors

On request

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).



LEATHER-LINE

LL LEGUAN Antigrav

Product characteristics

	NA
Base material	PP-glass fibres
Surface material	PU-leather
Material thickness mm	3,4
Temperature stability	up to 60 °C
Wet room suitability	■■■□
Rolled packable	–

Processing

	NA
Cutting, punching	✓
Drilling	✓
Sawing	✓
Milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	✓
Smallest bending radius	1000 mm

Extra equipment

	NA
Special formats	On request
Cuttings	✓
Magnetic from 3 sheets *	✓
PVA pre-treatment	–

Accessories

SIBUKLE	Spatula A2

Special colors

–

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).




LL LEGUAN Silver Antigrav
2600 x 1000 / **NA** 19781



LL LEGUAN Gold Antigrav
2600 x 1000 / **NA** 19778



LL LEGUAN Copper Antigrav
2600 x 1000 / **NA** 19777



LL LEGUAN Nero Antigrav
2600 x 1000 / **NA** 19779



LL LEGUAN Silk Antigrav
2600 x 1000 / **NA** 19780



LL LEGUAN Bianco Antigrav
2600 x 1000 / **NA** 19775



LL CORD Stony Ground Antigrav
2600 x 1000 / **NA** 19766




LL CORD Dove Tale Antigrav
2600 x 1000 / **NA** 19765



LL CORD Charcoal Light Antigrav
2600 x 1000 / **NA** 19764



2600 x 1000



LEATHER-LINE

LL CORD Antigrav

Product characteristics

	NA
Base material	PP-glass fibres
Surface material	PU-leather
Material thickness mm	3,8
Max. relief height mm	6,2
Temperature stability	up to 60 °C
Wet room suitability	■■■■
Rolled packable	–

Processing

	NA
Cutting, punching	✓
Drilling	✓
Sawing	✓
Milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	✓
Smallest bending radius	1000 mm

Extra equipment

	NA
Special formats	–
Further thicknesses	–
Cuttings	✓
Magnetic from 3 sheets *	✓
PVA pre-treatment	–

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A2

Special colors

On request



LEATHER-LINE

LEATHER-LINE Antigrav

Product characteristics

	NA
Base material	PP-glass fibres
Surface material	PU-leather
Material thickness mm	3,8
Temperature stability	up to 60 °C
Wet room suitability	■■■■
Rolled packable	–

Processing

	NA
Cutting, punching	✓
Drilling	✓
Sawing	✓
Milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	✓
Smallest bending radius	1000 mm

Extra equipment

	NA
Special formats	On request
Further thicknesses	–
Cuttings	✓
Magnetic from 3 sheets *	✓
PVA pre-treatment	–

* Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories


SIBUKLE	Spatula A2

Special colors


On request




LL Charcoal Dark Antigrav
2600 x 1000 / **NA** 19762



LL Charcoal Light Antigrav
2600 x 1000 / **NA** 19763



LL Dove Tale Antigrav
2600 x 1000 / **NA** 19769



LL London Clay Antigrav
2600 x 1000 / **NA** 19782



LL Stony Ground Antigrav
2600 x 1000 / **NA** 19794



DM CEMENT Dark Antigrav
2600 x 1000 / **NA** 19798



DECO-LINE

DM CEMENT Dark Antigrav

2600 x 1000



Product characteristics

	NA
Base material	PP-glass fibres
Surface material	impregnated paper
Material thickness mm	3,3
Temperature stability	up to 60 °C
Wet room suitability	■■■□
Abrasion resistance	■■■■□□
Rolled packable	–

Processing

	NA
Cutting, punching	✓
Drilling	✓
Sawing	✓
Milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	✓
Smallest bending radius	1000 mm

Extra equipment

	NA
Special formats	On request
Further thicknesses	–
Cuttings	✓
Magnetic from 3 sheets **	✓
PVA pre-treatment	–

Accessories

SIBUKLE	Spatula A2

Special colors

–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).



□ DM CEMENT Light Antigrav




DM CEMENT Light Antigrav
2600 x 1000 / **NA** 19563

DECO-LINE

DM CEMENT Light Antigrav

2600 x 1000



Product characteristics

	NA
Base material	PP-glass fibres
Surface material	impregnated paper
Material thickness mm	3,1
Temperature stability	up to 60 °C
Wet room suitability	■■■□
Abrasion resistance	■■■■■□
Rolled packable	–

Processing

	NA
Cutting, punching	✓
Drilling	✓
Sawing	✓
Milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	✓
Smallest bending radius	1000 mm

Extra equipment

	NA
Special formats	On request
Further thicknesses	–
Cuttings	✓
Magnetic from 3 sheets **	✓
PVA pre-treatment	–

Accessories

SIBUKLE	Spatula A2

Special colors

–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).



DM Travertin Antigrav
2600 x 1000 / **NA** 19567



2600 x 1000



DECO-LINE

DM Travertin Antigrav

Product characteristics

	NA
Base material	PP-glass fibres
Surface material	impregnated paper
Material thickness mm	3,3
Temperature stability	up to 60 °C
Wet room suitability	■■■□
Abrasion resistance	■■■■□□
Rolled packable	–

Processing

	NA
Cutting, punching	✓
Drilling	✓
Sawing	✓
Milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	✓
Smallest bending radius	1000 mm

Extra equipment

	NA
Special formats	On request
Further thicknesses	–
Cuttings	✓
Magnetic from 3 sheets**	✓
PVA pre-treatment	–

Accessories

SIBUKLE	Spatula A2

Special colors

–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).





DM MARBLE White Antigrav
2600 x 1000 / **NA** 19566

DECO-LINE

DM MARBLE White Antigrav

2600 x 1000



Product characteristics

	NA
Base material	PP-glass fibres
Surface material	impregnated paper
Material thickness mm	3,1
Temperature stability	up to 60 °C
Wet room suitability	■■■□
Abrasion resistance	■■■■■□
Rolled packable	–

Processing

	NA
Cutting, punching	✓
Drilling	✓
Sawing	✓
Milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	✓
Smallest bending radius	1000 mm

Extra equipment

	NA
Special formats	On request
Further thicknesses	–
Cuttings	✓
Magnetic from 3 sheets **	✓
PVA pre-treatment	–

Accessories

SIBUKLE	Spatula A2

Special colors

–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).



DM CONCRETE Grey Antigrav
2600 x 1000 / **NA** 22829



2600 x 1000



DECO-LINE

DM CONCRETE Grey Antigrav

Product characteristics

	NA
Base material	PP-glass fibres
Surface material	PP
Material thickness mm	3,3
Temperature stability	up to 60 °C
Wet room suitability	■■■□
Abrasion resistance	■■■■■■
Rolled packable	–

Processing

	NA
Cutting, punching	✓
Drilling	✓
Sawing	✓
Milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	✓
Smallest bending radius	1000 mm

Extra equipment

	NA
Special formats	On request
Further thicknesses	–
Cuttings	✓
Magnetic from 3 sheets**	✓
PVA pre-treatment	–

** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

Accessories

SIBUKLE	Spatula A2

Special colors

–



□
WL OAK TREE Light Antigrav

Photo: iStock.com



WL OAK TREE Light Antigrav
2600 x 1000 / **NA** 19561

WOOD-LINE

WL OAK TREE Light Antigrav

Product characteristics

	NA
Base material	PP-glass fibres
Surface material	impregnated paper
Material thickness mm	3,2
Temperature stability	up to 60 °C
Wet room suitability	■■■□
Abrasion resistance	■■■□□□
Rolled packable	–

Processing

	NA
Cutting, punching	✓
Drilling	✓
Sawing	✓
Milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	✓
Smallest bending radius	1000 mm

Extra equipment

	NA
Special formats	On request
Further thicknesses	–
Cuttings	✓
Magnetic from 3 sheets**	✓
PVA pre-treatment	–

Accessories

SIBUKLE	Spatula A2

Special colors

–

2600 x 1000



* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).



WL Nutwood Antigrav
2600 x 1000 / **NA** 19568



WL Nutwood Country Antigrav
2600 x 1000 / **NA** 19569



WL Maple Alpine Antigrav
2600 x 1000 / **NA** 19570



WOOD-LINE

WL Nutwood Antigrav

Product characteristics

	NA
Base material	PP-glass fibres
Surface material	impregnated paper
Material thickness mm	3,3
Temperature stability	up to 60 °C
Wet room suitability	■■■□
Abrasion resistance	■■■■□□
Rolled packable	–

Processing

	NA
Cutting, punching	✓
Drilling	✓
Sawing	✓
Milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	✓
Smallest bending radius	1000 mm

Extra equipment

	NA
Special formats	On request
Further thicknesses	–
Cuttings	✓
Magnetic from 3 sheets**	✓
PVA pre-treatment	–

Accessories

SIBUKLE	Spatula A2

Special colors


–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).



WL Wenge Wood Antigrav

Photo: © fotolia.com



WL Wenge Wood Antigrav
2600 x 1000 / **NA** 19571

WOOD-LINE

WL Wenge Wood Antigrav

2600 x 1000



Product characteristics

	NA
Base material	PP-glass fibres
Surface material	impregnated paper
Material thickness mm	3,3
Temperature stability	up to 60 °C
Wet room suitability	■■■□
Abrasion resistance	■■■□□□
Rolled packable	–

Processing

	NA
Cutting, punching	✓
Drilling	✓
Sawing	✓
Milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	✓
Smallest bending radius	1000 mm

Extra equipment

	NA
Special formats	On request
Further thicknesses	–
Cuttings	✓
Magnetic from 3 sheets**	✓
PVA pre-treatment	–

Accessories

SIBUKLE	Spatula A2


Special colors

–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).



WL Sessile OAK Antigrav
2600 x 1000 / **NA** 22785



2600 x 1000



WOOD-LINE

WL Sessile OAK Antigrav

Product characteristics

	NA
Base material	PP-glass fibres
Surface material	impregnated paper
Material thickness mm	3,3
Temperature stability	up to 60 °C
Wet room suitability	■■■□
Abrasion resistance	■■■■□□
Rolled packable	–

Processing

	NA
Cutting, punching	✓
Drilling	✓
Sawing	✓
Milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	✓
Smallest bending radius	1000 mm

Extra equipment

	NA
Special formats	On request
Further thicknesses	–
Cuttings	✓
Magnetic from 3 sheets**	✓
PVA pre-treatment	–

Accessories

SIBUKLE	Spatula A2

Special colors

–

* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).





WL Carbonized Wood Antigrav
2600 x 1000 / **NA** 20158

WOOD-LINE

WL Carbonized Wood Antigrav

Product characteristics

	NA
Base material	PP-glass fibres
Surface material	impregnated paper
Material thickness mm	3,3
Temperature stability	up to 60 °C
Wet room suitability	■■■□
Abrasion resistance	■■■■□□
Rolled packable	–

Processing

	NA
Cutting, punching	✓
Drilling	✓
Sawing	✓
Milling	–
Laser cutting	✓
Hot bending	–
PVA compressible	✓
Smallest bending radius	1000 mm

Extra equipment

	NA
Special formats	On request
Further thicknesses	–
Cuttings	✓
Magnetic from 3 sheets**	✓
PVA pre-treatment	–

Accessories

SIBUKLE	Spatula A2

Special colors

–

2600 x 1000



* Prior to printing a corona or plasma treatment has to be carried out. Upon request available in pre-treated version.
** Ground must be a SIBU metal foil SA (ref. 17637, self adhesive).

LEGENDE

PRODUCT CHARACTERISTICS
EXTRA EQUIPMENT
PROCESSING
ACCESSORIES

STORAGE / TRANSPORT GENERAL
CLEANING / DISPOSAL GENERAL

SIBU | DESIGN
we decorate.

Product characteristics

To answer your questions as quickly as possible, our team has worked out a technical table with product characteristics, extra equipment and much more for each of our products:

BASE MATERIAL

As a base material we use a specially developed, highly impact resistant polystyrene type (HIPS). HIPS distinguish particularly by robustness, high impact and a very low weight. For our ACRYLIC-LINE we use as a base material ABS with acrylic surface. With PUNCH-LINE 3D products we use HIPS with background foil from APET.
Scratch-resistant PMMA is employed for the SIBUGLAS product group and PP glass fibre material is used for the ANTIGRAV range.

- **HIPS = high impact polystyrene**
- **HIPS, PE foam = high impact polystyrene and Polyethylene foam**
- **ABS = Acrylonitrile butadiene styrene**
- **APET/HIPS = Amorphous polyethylene terephthalate and high impact polystyrene**
- **PP-glass fibre = Polypropylene with fiberglass**
- **PS = Polystyrene**

Reverse side of SIBUGLAS and OPACO-LINE panels:

- **PU-leather = Polyurethane synthetic leather surface**
- **Paper = printed paper**

MATERIAL THICKNESS

The given material thicknesses refer to the stock program in non adhesive (NA) and self adhesive (SA) version.

SA SELF-ADHESIVE

SA means that the design sheet is equipped with adhesive at the back. For this we use high-quality acrylic adhesive substance or synthesis rubber (PUNCH-LINE 3D, MultiStyle).
In order to achieve maximum adhesion, always clean non-absorbent surfaces with alcohol (ethanol, isopropyl alcohol).
Self-adhesive (SA) sheets are ideally suited to non-absorbent surfaces such as coated MDF/chipboard, glass, metal, plastic, etc. However, they are unsuitable for use on ceilings. Alternative processing options are available on request.

TOLERANCES

Machine-related dimensional and angle tolerances:
+/- 1.0 mm in relation to 1,000 mm

Temperature-related dimensional deviations:
+/- 0.7 mm in relation to 1,000 mm at a temperature change of 10 °C (except ANTIGRAV)

ROLLED PACKABLE

Basically our design sheets are packed flat on pallets. However, in order to dispatch small consignments as favourably as possible, we have developed a packaging carton in which many of our design sheets can be packed rolled as well.

Basically, the following applies:
Design sheets in non-adhesive (NA) version are rolled with the decor side outwardly and design sheets in self-adhesive version (SA) are rolled with the glue side outwardly.

Exceptions:
LEATHER-LINE, FABRIC-LINE, DM DEEP BRUSHED and DM CONCRETE products as well as sheets with a magnetic film: always roll with the patterning on the outside.

PL3D, WOOD-LINE and DECO-LINE products with impregnated papers such as DM GENESIS Grey supermatt AR, DM GENEIS White supermatt AR, DM MARBLE White supermatt AR and DM MARBLE Black supermatt AR: always roll with the patterning on the inside.

Packed in boxes (480x480 mm):
Sheets with a magnetic film: we recommend a maximum of 2 pieces per box.

DECO-LINE products with impregnated paper as well as DM DEEP BRUSHED, DM CONCRETE, DM GENESIS Grey supermatt AR, DM GENEIS White supermatt AR, DM MARBLE White supermatt AR and DM MARBLE Black supermatt AR, LEATHER-LINE, FABRIC-LINE, PUNCH-LINE 3D and WOOD-LINE: we recommend a maximum of 3 pieces per box.

DECO-LINE (excluding products with impregnated paper as well as DM DEEP BRUSHED, DM CONCRETE, DM GENESIS Grey supermatt AR, DM GENEIS White supermatt AR, DM MARBLE White supermatt AR und DM MARBLE Black supermatt AR), WOOD-LINE, PUNCH-LINE, ACRYLIC-LINE, MSC and STRUCTURE-LINE products: we recommend a maximum of 6 pieces per box.

After receipt, rolled goods should be laid out flat for around 24 hours at room temperature and if necessary, subjected to additional weight.

SURFACE MATERIAL

In a changeable world we focus on lastingness and high standards by using 100% PVC-free surfaces. We make a distinction between:

- **PU-leather = Polyurethane synthetic leather surface / Artificial leather surfaces**
- **PMMA = Polymethyl methacrylate**
- **PMMA AR+ = Polymethyl methacrylate with AR + scratch resistant coating**
- **impregnated paper = paper with protective varnish**
- **Print**
- **PET = Polyethylene terephthalate (UV lacquer for the AR version)**
- **PET/Faser = Polyethylene terephthalate (Artificial fur surfaces)**

All variations are optically outstanding and also fascinate by their unique haptics. They correspond to the highest demands and they are suited especially for the interior area.

MAXIMUM RELIEF HEIGHT

With the given data we define the highest position of the respective design in non-adhesive (NA) and adhesive (SA) version.

PRINTING

Owing to the many differing printing and colour systems, customers must carry out a printing test. The result will depend on the respective motif. We will be pleased to provide original samples for testing.

SIBU guideline values:

PRD digital printing possible
PRS screen printing possible
PR+ digital/screen printing possible
PR+* digital/screen printing possible, prior to printing a corona or plasma, treatment has to be carried out. By request available in pre-treated version.
PRS* screen printing possible, prior to printing a corona or plasma, treatment has to be carried out. By request available in pre-treated version.

SCREEN PRINTING:
The final adhesion performance will set in very slowly and can take up to one week on air-drying (20 °C.).

TEMPERATURE STABILITY

We supply to more than 70 countries in the world and have nearly everywhere special climate situation. Therefore we test our material under the hardest conditions. Already during development stage our SIBU DESIGN sheets are tested in special thermo-containers stuck on ground as well as unstuck with high temperatures and high air humidity.
Only the very best qualities correspond to our strict directives. The given data of the temperature stability refer to the lasting application of the product stuck on different grounds and to the long-term using temperature also without adhesion.

WET ROOM SUITABILITY

An exposure of SIBU DESIGN sheets to humid areas is given when a design sheet is subjected to short term humidity condition. This humidity condition can occur by reason of high air humidity or by direct sprinkling water. SIBU DESIGN sheets are not suited for the direct wet space area as well as for long-term wet influence (except SIBUGLAS).

■■■■ Wet room suitability

■■■□ Wet room suitability, but material reacts more sensitively to sprinkling water. Removing of moisture is recommended.

ABRASION RESISTANCE

Products with marked abrasion resistance **AR** show an extremely abrasion resistant surface. Our technology team already tests the products during development process to be able to offer the matching product for each of your demands.

■■■■■■■■ Scratch resistant (SIBUGLAS AR+)
■■■■■■ Excellent abrasion resistance
■■■■■□ Very good abrasion resistance
■■■■□□ Good abrasion resistance
■■■□□□ Normal abrasion resistance
■■□□□□ Low abrasion resistance
■□□□□□ Use only in the decoration area

Extra equipment

We are aware of the fact that not always you can use our standard stock articles for your intended application and offer for you special extra equipment.

FIRE CLASSIFICATION

The products from the stock program correspond to the fire safety regulations according to DIN 4102 B2, excluded products ACRYLIC-LINE (test standard: UL Standard 94, measured value: 94 HB). Marked products **FR** are available in flame retardant version on request, on a different carrier material. Manufacturer's certificate of compliance of the following standards are available: EN 13501-1 and ASTM E 84. Info sheets on demand!

CUTTINGS

You want to get customized sheets or cuttings? Please contact us that we can offer the best possible solution to you. With a cutting length up to 3.2 meter and a punching and sawing length up to 3 meter we are able to meet your requirements and needs promptly.

PVA PRE-TREATMENT

In order to be suitable for PVA bonding, depending upon the material thickness on the reverse side, SIBU DESIGN sheets either have to be pre-treated by means of an additional production process, or roughened by using a vibration sander (80-grain sandpaper).

Being able to carry out this pre-treatment for you in our factory, we absolutely need this information together with your order.

SPECIAL FORMATS

In addition to the standard sizes given in the OVERVIEW we offer with pleasure individually adapted product dimensions.

FURTHER THICKNESSES

Responding to your request we produce our DECO-LINE and PUNCH-LINE in thicknesses between 0.8 and 4.0 mm.

MAGNETIC

All SIBU DESIGN sheets are available with a magnetic back from 3 pieces onwards. Exception - all LL ROMBO, LL QUADRO, LL CRISTAL ROMBO, PUNCH-LINE and SIBUGLAS Hollywood.

SIBU magnetic foils are suitable on different metallic grounds and on magnetic colours. The exchange of design sheets thereby becomes a child's play! The application fields for the SIBU DESIGN magnetic program are nearly unlimited – for shop-window decoration, shop fitting and fair design or in the furniture area, decoration field and for all kinds of displays.
Self-adhesive SIBU metal film is employed when a suitable metallic ground is lacking. The metal film can be ordered as a sheet (2,600x1,000 mm) or roll (14 or 29 m)

Processing (except SIBUGLAS, OPACO-LINE and ANTIGRAV)

Please note that SIBU DESIGN sheets always have to be processed from the decor side.

SURFACE PROTECTION

A protective film (Polyethylen/PE) protects our surfaces against damages. This protective film should be removed only after the application of our design sheets.
The following products are delivered without a protective film:
DM MONSOON Vintage Brown and all products of the FABRIC-LINE.

PUNCHING

Band steel cutting is recommended for design sheets in thickness from 1 up to 1.5 mm.
Please study the technical table in the OVERVIEW in order to see if this processing step is permissible for your product.

DRILLING

All SIBU DESIGN sheets can be drilled from the decor side.

MILLING

For material up to 2 mm thickness:
Cutter with 3 mm diameter, rotation speed from 12000 up to 24000 rpm, progressive feed up to 12 m/min.
Decor side on top:
milling cutter with a left-hand twist, cutting right.
Decor side below:
milling cutter with a right-hand twist, cutting right.
For material with a thickness of more than 2 mm, reduce the progressive feed and use a milling cutter with a larger diameter (6 mm).

SMALLEST BENDING RADIUS

The given data refer to the smallest bending radius for concave or convex fixing. For all design sheets – with the exception of MultiStyle – all sheet edges must be fixed mechanically in any case! For MultiStyle there is no need for mechanical fixing!

HOT BENDING

Heat up the SIBU DESIGN sheets from the backside – for both, internal and exterior angles.

Approximate parameters for material in 1mm thickness:
wire temperature: approx. 200°C, heating time: approx. 6-17 seconds - depending on the surface material.

For ACRYLIC-LINE, PUNCH-LINE, DECO-LINE, STRUCTURE-LINE and FABRIC-LINE design sheets hot bending is outwardly (decor outside = external angle) possible – hot bending inwards (decor inside = interior angle) is possible only with plain designs or with fine structures.
For deeper structures - no exact internal angle.

Hot bending with LEATHER-LINE design sheets is possible outwardly (decor outside = external angle), inwards (decor side inside = interior angle) only with plain LEATHER-LINE. Using structured leather designs it can happen that wrinkles may appear along the internal angles.

CUTTING

SIBU DECO-LINE sheets with less than 2 mm thickness can be easily cut with a wallpaper knife. Simply notch the surface and break along the edge. For all other product lines and for DECO-LINE sheets up to 3 mm thickness the cutting pressure has to be increased. After cutting and breaking our self-adhesive (SA) design sheets as well as 3D PUNCH-LINE designs (NA + SA) the foil on the back side has to be cut separately.
Always use well sharp knives.

SAWING

SIBU guideline values:
Material thicknesses of up to 1 mm:
HW 280x3.2 / 2.2x30 Z60 / 12.46-18.08 WZ

Thicker than 1 mm:
HW 250x3.2 / 2.2x30 Z40 / 19.63 WZ/FA
HW 250x3.2 / 2.2x30 Z40 / 19.63 FZ/TR
(speed 6000 rpm, progressive feed of up to 25 m/min).

For LEATHER-LINE / FABRIC-LINE:
HW 255x2.8 / 2.0x30 Z80 / 10.01 FZ WZ
(speed 6000 rpm, progressive feed of up to 10 m/min).

The best result with LEATHER-LINE and FABRIC-LINE is achieved with MDF underlay (4 mm) above and below, slow progressive feed and high speed.

*HW (hard metal material), WZ/FA (alternating teeth/bevelled edge), FZ (flat teeth), TR (trapezoidal teeth)

LASER CUTTING

All SIBU DESIGN sheets can be processed with standard lasers.
The cutting speed conforms to the watt power of the laser.

Please refer to the technical data in our OVERVIEW broschure, if that processing step is permitted for that product.

THERMOFORMING

With a variety of Deco-Line products light forming, by using flat and not sharp-edged tools, is possible (avoid sharp contours and use larger radii). With every new moulding test are to be made, in order to obtain ideal results. The tool must be adapted to the material.

Refer to the technical table in the OVERVIEW catalogue whether this processing step is suitable for your product or not.

PVA-PRESSING

Non-adhesive design sheets from our DECO-LINE, LEATHER-LINE, FABRIC-LINE, STRUCTURE-LINE, ACRYLIC-LINE and ANTIGRAV series (with a few exceptions) are compressible with commercial PVA adhesives. The ground must be absorbent (MDF, chipboard, etc.)

In order to be suitable for PVA bonding, depending upon the material thickness on the reverse side, SIBU DESIGN sheets either have to be pre-treated by means of an additional production process, or roughened by using a vibration sander (80-grain sandpaper).

Should by reason of transport or stock conditions the design sheet not have a crease-free protective film, the film should be removed prior to pressing process. The pressure applied should amount to 2 kg/cm² (0.2 N/mm²), the temperature to approx. 45°C and the pressing time to around 10 minutes. The bonding of the balancing material and the design sheet should be done in a single working process.
During pressing onto an untreated particle board in 16 mm thickness, best results were achieved with a 1 mm polystyrene balancing sheet.

When pressing structured design sheets (STRUCTURE-LINE, ACRYLIC-LINE, FABRIC-LINE and LEATHER-LINE), a medium-hard sponge rubber mat with a thickness of approx. 5 mm should be used between the pressing sheet and the patterned side of the design sheet. This provides uniform pressure distribution and prevents undesirable crushing spots.

When using DECO-LINE sheets it is better to press without the sponge rubber mat. The mat could cause irregular optics in the mirror surface. If you want to have a perfect mirror result, ask us for design sheets in 2 mm thickness.

Following pressing allow the sheets to cool in a stack over night (about 16 hours). Cover the stack with a 19 mm plate so that the uppermost sheet also remains flat.

As a result of this type of processing, standard edges of plastic, aluminium or wood can be used! The PVA adhesive prevents the usual expansion of our design sheets due to the effect of increased temperature!

PVA pretreated products should be processed within the specified processing period (see PVA News Update at www.sibu.at).

Accessories

SIBUKLE D22HV

Solvent-free dispersion adhesive
The best suitable spatula size A1 or A2 is given for each product.

Applications: SIBUKLE is highly suitable for the bonding of SIBU products onto absorbent, flat surfaces such as wood, plywood, particleboard, gypsum plasterboard, concrete or smooth brickwork.

WARNING: SIBUKLE is entirely unsuitable for non-absorbent surfaces such as tiles, plastics, metals, glass, etc.

Please follow the processing guidelines on the adhesive label.

Storage / Transport

STORAGE INSTRUCTIONS

SIBU DESIGN sheets must always be kept in indoor stock, no storage outside! Following instructions are to be considered:

- Design sheets to be stored flat, rolled packed design sheets should be unpacked and laid out flat and - if necessary - subjected to additional weight to improve flatness (Use carton underlay and weigh down the entire sheet in order to prevent damage.)
- Store the uppermost plate in the pile with decor side down.
- Protect SIBU products from UV rays.
- Do not expose SIBU products to moisture or humidity.
- Protect material from dirt, dust and mechanical damages.
- A permanent storage of more than 3 months at a temperature less than 0 °C or more than +30 °C may impact the quality of our design sheets and should be avoided.

TRANSPORT INSTRUCTIONS

In general, for the transport of SIBU products pay attention to protect them from dirt, UV radiation, moisture and mechanical damages.

- Use stable, flat pallets with carton bedding, the pallet should be longer than the design sheets.
- Place the uppermost design sheet on the pallet with the decor side face down. This uppermost design sheet should be protected in addition by a carton and a board (e.g., chipboard, HDF…).
- The design sheets should be protected from shifting.
- The edges and sides must be also protected (edge protection, PE foil …)
- Avoid temperatures below – 35 °C or more than + 50 °C.
- Structured sheets to be transported on pallets with the patterns running in same direction.
- SIBU products must be acclimatized prior to processing; ideal processing temperature is approx. + 10 °C to + 30 °C.
- Before any processing of the design sheets read the attached processing instructions which you can also find on the SIBU website!
- SIBUKLE should not be long-time stored below + 5 °C and must be protected from frost during transportation.
- Rolled packable: please see page 170

Cleaning / Disposal

CLEANING

Do not use abrasive cleaners, solvent cleaners or pure alcohol!

DECO-LINE, STRUCTURE-LINE, ACRYLIC-LINE, PUNCH-LINE, PUNCH-LINE 3D: in case of light dirt by means of soft cleaning cloth (it should be free of dust and free of dirt). In case of heavy dirt by means of standard plastic or window cleaner (spray cleaners not onto the material surface, but sparingly onto the cleaning cloth).

LEATHER-LINE: Clean leather surfaces by means of standard liquid soap and then remove the soap with a humid cloth.

FABRIC-LINE: Stains caused by oil, greases and ink must be removed immediately. Vacuum the surface in case of low pollution; in case of heavy pollution, dab the stain with an absorbent cloth, then wipe it off with mild soapy water.

DISPOSAL

The keeping of healthy environment has high priority for us! We check all raw materials used for their environmental compatibility. Because not everyone has its own plastic disposal container, we pay special attention in development of new products to use only high-quality materials: materials, which may be disposed safely with the domestic waste. On demand we are pleased to provide LGA certificates for all SIBU DESIGN sheets.

PROCESSING INSTRUCTIONS GENERAL

PROCESSING INSTRUCTIONS **SIBU**GLAS / OPACO-LINE

PROCESSING INSTRUCTIONS **ANTIGRAV**

SIBU | DESIGN
we decorate.

Processing information general
(except SIBUGLAS, OPACO-LINE und ANTIGRAV)

GROUND PREPARATION FOR GLUING

The ground must be dry and smooth, and free from loose material, dust, dirt, grease, wax and silicone. SIBU DESIGN patterned sheets should never be mounted onto an uneven surface, as this results in a loss of visual quality.
In the case of convex and concave surfaces, the sheet edges must be fixed mechanically (except for MultiStyle).

Non-absorbent surfaces
In order to achieve maximum adhesion, always clean non-absorbent surfaces with alcohol (ethanol, isopropyl alcohol).
Self-adhesive (SA) sheets are ideally suited to non-absorbent surfaces such as coated MDF/chipboard, glass, metal, plastic, etc. However, they are unsuitable for use on ceilings. Alternative processing options are available on request.

Absorbent surfaces
A solvent-free adhesive, which is suitable for both the underlying surface and the polystyrene material (base material), must be employed on absorbent grounds, e.g. uncoated chipboard, MDF, plasterboard, or smoothed brickwork. SIBU DESIGN recommendation: SIBUKLE.

BONDING

Patterned sheets delivered in rolled form must be kept flat for a minimum of 24 hours. Weighing down improves evenness.

Ideal processing temperatures range from + 10°C up to + 30°C. The design sheets should be acclimatised, i.e. be brought to room temperature prior to processing (avoidance of condensation on the gluing surface and a reduction in sheet expansion due to reduced temperature differences).

A temperature increase of 10°C will cause our products to expand by approx. 0.7 mm over a length of 1 meter. As a rule, expansion gap of approx. 2 – 3 mm should be kept at each sheet edge!

In case of high surroundings temperature or major temperature-fluctuations the expansion gap should be increased or the sheet format should be chosen smaller.

Remove the backing cover step-by-step from self-adhesive design sheet (SA), do not touch gluing surface and press the sheet onto the ground as firmly as possible. Avoid blistering (air inclusions); use a medium-hard hand rubber roller with a width of approx. 170 mm. The final adhesion power will be reached at room temperature after 24 hours.

PROCESSING SIBUKLE

Application: SIBUKLE is ideally suited to the bonding of SIBU DESIGN products onto absorbent, even surfaces such as wood, MDF, plywood, chipboard, plasterboard, or smooth brickwork. The underlying surface must be absorbent (MDF, chipboard, etc.).
WARNING! SIBUKLE is not unsuitable for non-absorbent grounds such as tiles, plastics, metals and glass, etc.
As a rule, an approx. 2 to 3 mm expansion joint is to be left along the sheet edges!

Processing: Apply only to the cleaned surface, which has been prepared for bonding, using a fine spatula (the spatula toothing for every product is provided in the OVERVIEW catalogue). With an ambient temperature of between 20 °C and 35 °C, the adhesive should then be left to air for 20 to 40 minutes. No drying time is required for PNL products, which are to be bonded in a wet adhesive bed. Fix mechanically if necessary, until the adhesive has hardened.
The higher the ambient temperature, the shorter is the airing time.
Finger test: following application with the spatula, the optimal airing time is reached as soon as the adhesive no longer sticks to the fingers!
Avoid the formation of bubbles (air inclusions) and use a medium-hard, rubber roller with a width of approx. 170 mm.

If other solvent-free dispersion adhesives are employed, the respective processing instructions are to be followed.

Storage: In the original airtight containers the adhesive can be stored up to 12 months from delivery date. Store always above freezing point. Protect from frost, otherwise the glue cannot be used anymore!

GROUNDS – BONDING – EXPANSION GAPS

The ground must be dry and smooth, and free from loose material, dust, dirt, grease, wax and silicone. SIBU patterned sheets should never be mounted onto an uneven surface, as this results in a loss of visual quality.
In the case of convex and concave surfaces, the sheet edges must be fixed mechanically.

Non-absorbent surfaces:
In order to achieve maximum adhesion, always clean non-absorbent surfaces with alcohol (ethanol, isopropyl alcohol).
Self-adhesive (SA) sheets are ideally suited to non-absorbent surfaces such as coated MDF/chipboard, glass, metal, plastic, etc. However, they are unsuitable for use on ceilings. Alternative processing options are available on request.

Absorbent surfaces:
A solvent-free adhesive, which is suitable for both the underlying surface and the polystyrene material, must be employed on absorbent grounds, e.g. uncoated chipboard, MDF, plasterboard, or smoothed brickwork. Sibu recommendation: SIBUKLE D22 HV.

Ideal processing temperatures range from + 10 °C to + 30 °C. The design sheets must be acclimatised, i.e. be brought to room temperature prior to processing (avoidance of condensation on the gluing surface and a reduction in sheet expansion due to reduced temperature differences).

A temperature increase of 10 °C will cause our products to expand by approx. 0.7 mm over a length of 1 m.

As a rule, an approx. 2-3 mm expansion joint is to be left along the sheet edges!

In the case of high ambient temperatures, or major temperature fluctuations, the expansion gap should be increased, or a smaller sheet format selected.

Remove the paper backing from the reverse side of self-adhesive patterned sheets (SA) step-by-step. Do not touch the adhesive surface and press the sheet onto the ground as firmly as possible. Avoid the formation of bubbles (air inclusions) and use a medium-hard, rubber roller with a width of approx. 170 mm.

Full adhesion will be reached at room temperature after 24 hours.

Whenever possible, SIBU DESIGN products should be processed within 12 months (except for PVA pre-treated products, please see the PVA news update at www.sibu.at).

They are not recommended for use near open fires or sources of intense heat.

BONDING USING SIBUKLE

SIBUKLE is suitable for the bonding of SIBUGLAS AND OPACO-LINE products on absorbent, level surfaces such as wood, plywood, chip- and plasterboard, concrete or smoothed masonry. PLEASE NOTE: SIBUKLE is totally unsuitable for non-absorbent surfaces such as tiles, plastic coverings, metal, glass, etc.


Processing: once the ground surface for laying has been prepared and cleaned, fully cover it alone with adhesive using a spatula with A2 teeth and then press down. It is essential that products be bonded in a bed of wet adhesive. When required fix mechanically until the adhesive has hardened. Please follow the processing guidelines on the adhesive label.

BONDING & POINTING WITH SIBU SILICON

(Acetic acid free, textured natural stone silicone)

Bead bonding:
On the reverse side of the sheet: vertical positioning of a silicone bead at a distance of 10 mm from the edge of the sheet or the profile leg, then position a mirrored adhesive tape at a distance of 10 mm.
It is recommended that the protective strip on the mirrored tape be removed prior to the further processing phases.

Apply vertical beads of adhesive to the reverse side of the sheet at intervals of approx. 10 mm to the mirrored adhesive tape. (Depending on the underlying surface, the beads should have a height of at least 4 mm.) Apply the other silicone beads at a distance of 60 mm.



The illustration does not show the entire length of the panel

Bring the sheet into position without any drying time and then press it down onto the prepared surface by means of vertical strokes with a soft wallpaper roller.
The gluing can also be done without mirror adhesive tape!
Advantage: The sheet can be positioned much easier.
Disadvantage: The sheet has to be temporarily attached until the silicone beads have cured in order to prevent the plate from slipping unintentionally.

Once the adhesive has hardened, the joints can be sealed with silicone.

Immediately remove the protective film from the sheet and any possible adhesive residues.

PVA BONDING

(please see page Seite 184)

MAGNETIC

With the magnetic finish professional decoration changes become a child's play. Deliveries can be made for orders of three sheets and upwards. Any surfaces suitable for magnets can be used as a ground and should these be unavailable, SIBU METALFOIL provides the solution.

SURFACE PROTECTION

All the top surfaces are safeguarded against damage by a protective film (Polyethylen/PE), which should first be removed following processing.

GOLDEN RULES

As a rule, complete processing on the patterned side (for this reason jig- and hand-held circular saw working must take place on the reverse side).

It is imperative that sheet flapping be avoided totally during all working phases.

Always lay the sheets out flat and if necessary pin them down.

Select the speed and feed that are adapted to the saw blade. Use sharp cutting tools!

The generation of heat should be constantly avoided, as this can result in material tension.

MECHANICAL PROCESSING OF THE PATTERNED SHEETS PRIOR TO ADESIVE APPLICATION

Sawing
Sheets can be cut with jig, hand-held circular, panel and circular table saws. During cutting on the reverse side, the underlay should also be sawn through. Then deburr all cut edges.

- **Cutting to length using a hand-held or plunge cut circular saw**

  Cut from the reverse side and use a stable underlay.

  Recommended saw blade: 160x2.2 hard metal blade with 48 alternating teeth.

- **Cutting to length using a jigsaw**

  Set the pendulum action to zero, or at a maximum to 1 and then saw from the reverse side.

  The patterned sheet must lie fully on the jigsaw cutting table in order to ensure that no vibrations are created.

  Recommended saw blade: employ saw blades with a tooth pitch of 1.2 to max. 2.5 mm. (coarse metal saw blade / fine wood saw blade / preferably PMMA saw blades).

Drilling
All drillings must be carried out on a stable underlay.
Recommended drill: wood drill (centring tip drill), Forstner drill and hard metal drill with centring tip.
Core drills for wood or hole saws (BI-metal) can also be used. Fix the design sheet on a stable surface.

FLAMMABILITY

SIBUGLAS / OPACO-LINE products are subject to standard flammability
pursuant to EN 13501-1 Class E.

LASER CUTTING

Design sheets can be processed using standard lasers. The cutting speed is in line with the laser wattage.

Note: Place the design sheet on the laser machine in such a way that its reverse side is on the machine's extraction side. As is the case with all standard PMMA products, it is recommended that following laser cutting the material be "tempered". The high temperature of the laser causes tension in the material, which can lead to cracking. Tempering equalises these tensions.

PRINTING

SIBUGLAS: digital/screen printing possible

OPACO-LINE: screen printing possible. Prior to printing a corona or plasma treatment has to be carried out. On request available in pre-treated version.

Owing to the many differing printing and colour systems, customers must carry out a printing test. The result will depend on the respective motif. We will be pleased to provide original samples for testing.

CLEANING / CARE

Standard household cleaners without scouring agents can be used.

DISPOSAL

Current LGA certificates exist for SIBUGLAS and OPACO-LINE. We are pleased to make these available.
Private area: Sheets an be disposed of with the normal household refuse.

Commercial area: Sheets should be conducted to thermal disposal.

STORAGE INFORMATION

Always store products dry and flat, and protect them against the effects of humidity.

Wrap the sheets in plastic together with a silicate cachet and seal carefully. This prevents possible ripples along the sheet edges due to moisture in the air.

Outdoor storage is not possible

The following should be noted:
In order to prevent damage, the card underlay should be used and weighed down over its entire area. The uppermost sheet in the stack should be stored face down.

In storage, design sheets must be protected against sunlight and do not expose to wetness of damp.

The material should also be safeguarded against dirt, dust and mechanical damage.

TRANSPORT INFORMATION

When transporting SIBUGLAS / OPACO-LINE care should be taken that the sheets are protected against dirt, UV rays, moisture and
mechanical damage.

Stable, flat pallets that are larger than the sheets are to be employed with a card underlay.

The uppermost sheet must lie on the pallet with the structured face down. In addition, this top sheet should be protected by card and a slatted frame.

The edges and the sides must also be safeguarded (edge protection, PE film, …).

The temperatures below minus 35° C or above 50° C should not be exceeded.

SIBUGLAS SA, OPACO-LINE SA -
BONDED ONTO COATED WOOD BASED SHEETS INCLUDING EDGES AND MILLING

MATERIAL REQUIREMENTS

SIBU decorative sheet:

SA dimension: 2600 x 1000 mm, self-adhesive

Wood based sheet:
Wood based sheet coated on both sides, dimensions: 2600 x 1000 mm


Counter-pressure:
Not required

Edge material:
All standard furniture edging

PROCESSING STEPS

1. Clean the coated wood sheet.
2. Remove the protective film on the adhesive side of the design sheet.
3. Bond the design sheet onto the wood based sheet using a rubber roller.
4. Immediately cut the bonded sheets into the desired final dimensions (saw).
5. Place the edgings on the edge gluing machine.
6. **Using an electrical manual router, cut a rounded or chamfered edge exactly up to the point of transition from the transparent PMMA layer/PS layer to the structured layer. Please see sketch!** In combination, the edge material and the transparent PMMA layer/PS layer give the resultant radius or chamfer. The thicker the edge material, the wider the facet.

FACET MILLING IS THE PREREQUISITE FOR AN EDGED END PRODUCT!





SIBUGLAS AND OPACO-LINE PVA
GLUED AND PRESSED ON ABSORBENT WOOD BASED SHEETS

Whether on home furniture, in display windows, bars, hotels, or trade fair stands, today SIBUGLAS and OPACO-LINE is used for a diversity of applications.
SIBUGLAS is a multilayer sheet comprised of PMMA, PU leather, a special synthetic leather or a special paper. The OPACO-LINE is a multilayer sheet comprised of a matt polyester surface, a polystyrene carrier and a special paper. This multilayer sheets can be bonded onto absorbent surfaces using PVA white glue. In order to ensure optimum flatness, we also deliver an accompanying, technically matching balancing sheet.

PROCESSING

Both reverse sides (design and balancing sheet) are saturated with PVA white glue as evenly and quickly as possible using a roller. They are then laid on both sides of the absorbent wood based sheet and this composite is subsequently placed in a sheet press.

DESCRIPTION – STRUCTURE

SIBUGLAS / OPACO LINE decorative sheet

PVA white glue

Wood based sheet
minimum thickness of 16 mm!
Use thicker wood based sheets for larger formats!

PVA white glue
Balancing sheet



Decorative sheets that have been glued and pressed in this manner can be easily processed with the majority of woodworking machinery and tools with good results. The PE protective film must be left on the top surface during processing. Optimum machine parameters, tool layout and cutting speeds are to be determined individually prior to production on the basis of a sample.

BONDING INSTRUCTIONS FOR SIBUGLAS SHEETS WITH PVA WHITE GLUE

Glue application: only use flat, wood based sheets!
The acclimatised design and balancing sheets, as well as the wood based sheet, should be laid out adjacent to one another on a straight, clean and sufficiently large work table. The wood based sheet must be roughly cut 10mm larger than the design sheets / balancing sheets. **Both sheets - the design sheet and the balancing sheet - should first be generously coated with PVA glue using a roller.** Owing to the highly absorbent reverse side, the consumption of PVA white glue is considerable. Subsequently, both sheets (design sheet and balancing sheet) are positioned as quickly as possible on the middle of the wood based sheet.

! Warning! Glue should not be applied directly to the wood based sheet, as this can have a negative effect on evenness!

Pressing:
The composite sheet is now placed in the press for approx. 30 minutes at 30° C. Do not apply excessive pressure and take into account both your know-how and the values gained from personal experience. Standard value: 20 N/cm^2 or 2 kg/cm^2.

As soon as the sheets are removed from the press, they must be stored under **stacking pressure for at least 12 hours in a FLAT position.** A genuinely even surface is extremely important for the flatness of the composite sheet!

A second possibility for small batches is to press the sheets in the machine overnight at approx. 20° C. This type of processing eliminates the need for subsequent stack pressure.

Always clean the press thoroughly prior to processing sheets!

Cutting to length/edge trimming and other processing steps:
With standard woodworking machines:
Recommendation: Fine cut saw blades

At the earliest, complete this work 12 hours after gluing/ pressing!

Edging application: As usual, any standard edging can be mounted in the familiar manner!

BALANCING SHEET

A technically matching balancing sheet is required for the glued and pressed composite (surface + wood based sheet + counter-pressure) that is ideally matched to the characteristics of the materials used. This virtually rules out warping due to heat, cold or fluctuating humidity.


For SIBUGLAS and OPACO-LINE (PMMA 2 mm) we recommend the use of the **PMMA Balance Sheet White 2800x1250x2** (article number: 20278) for balancing.

If the PMMA Balance Sheet White has not been pressed within six months, we recommend a check on the surface tension of the reverse side and if required, its subsequent surface treatment.


Processing ANTIGRAV

Standard processing


ANTIGRAV can be bonded edge to edge and therefore does not require expansion joints.
Readjustment on **any surface** is no problem when bonding with standard silicon or hybrid polymer adhesive is employed.
ANTIGRAV can be cut to size by using standard cutting-tools. Processing to be executede from the patterned side.




Processing to be executed from the patterned side.



Apply beads of silicone vertically (1cm from the edge and with 6cm-spaces between the individual beads).



Press the sheet onto the wall and then adjust it.



Bonding is edge to edge = 0mm expansion joint

NA
non-adhesive

SA
self-adhesive

FR
flame-retardant version available on request

PRD
digital printing possible

PRD*
digital printing possible
Prior to printing a corona or plasma treatment has to be carried out.
By request available in pre-treated version.

PRS
screen printing possible

PRS*
screen printing possible
Prior to printing a corona or plasma treatment has to be carried out.
By request available in pre-treated version.

PR+
digital/screen printing possible

PR+*
digital/screen printing possible
Prior to printing a corona or plasma treatment has to be carried out.
By request available in pre-treated version.

■■■■
wet room suitability

■■■□
limited suitability for wet rooms

AR
abrasion-resistant

AR+
scratch-resistant

+ ▼
entire panel length not shown in image

Continuous pattern
Continuous pattern

SIBU | DESIGN
we decorate.

This information tool was provided according to the best knowledge and with special care. The information is based on practical experiences, test results as well as on in-house testing and corresponds to our today's state of knowledge. Detailed info sheets are available on request. No liability is accepted for misprints, norm errors and mistakes!



SIBU DESIGN GmbH & Co KG
Jupiterstraße 8 / 4452 Ternberg, Austria
T. 0043 (0) 7256 / 6025-0 / F. 0043 (0) 7256 / 7020
info@sibu.at / www.sibu.at